

Specifications

Frequency Range (-10dB)	39 Hz - 18 kHz
Coverage Pattern (-6dB)	/64: 60° Horizontal x 40°Vertical/95: 90° Horizontal x 50°Vertical
System Input Power Rating	LF: 2 x 800 W Continuous (IEC / 100 hour)MF: 270 W Continuous (IEC / 100 hour)HF: 100 W Continuous (IEC / 100 hour)
Maximum Peak Output *2	/64: 143dB (Preset: F35/64 FR)/95: 143dB (Preset: -F35/95 FR)
System Processing	Crown Audio I-Tech HD SeriesCrown Audio I-Tech 4x3500HD
System Impedance	LF = 2 x 8 ohms MF = 8 ohms HF = 8 ohms
LF Driver	2 x 2265H, 254 mm (15 in) diameter, dual 76 mm (3 in) diameter voice coil, NDD®, Direct Cooled™
MF Driver	1 x 2169H, 203 mm (8 in) dia., 76mm (3 in) Dual Voice Coil, Neodymium Differential Drive®, Direct Cooled™
HF Driver	1 x D2430H, D2 dual diaphragm, dual 76mm (3 in) diameter voice coil
Enclosure	18 mm, 11-ply Finnish birch plywood; black DuraFlex™ finish; integral recessed handles
Grille	Powder Coated 14 gauge hex-perforated steel with acoustically-transparent black cloth backing
Input Connectors	Neutrik® Speakon® NL-8 (2x): LF1: 1± LF2: 2± MF: 3± HF: 4±
Dimensions (H x W x D)	1051.5mm x 568.9mm x 528.3mm (41.4in x 22.4in x 20.8in)
Net Weight (each)	52.6 kg (116 lbs)

System Type	High Performance Dual 15" 3-Way Loudspeaker with 90 x 50 degree coverage
Suspension / Mounting	Integrated M10 mounting points