

Specifications

System Type	3-Way High Directivity Line Array Element with D2 Technology
Frequency Range (-10dB)	60 Hz – 20 kHz (Preset: VTX V20)
Horizontal Coverage (-6 dB)	105 degrees nominal (300 Hz - 16 kHz)
Maximum Peak Output	139 dB (Preset: VTX V20)
System Amplification	Crown Audio I-Tech HD
Nominal Impedance	Active: LF: 2x 8 ohms MF: 8 ohms HF: 8 ohms Passive: LF: 16 ohms MHF: 8 ohms
LF Driver	(2) JBL 2161H 10-inch Neodymium Differential Drive® woofer
MF Driver	(4) JBL 2164H 5-inch Neodymium mid-range woofer
HF Driver	(3) JBL 2415K D2 Dual Diaphragm, Dual Voice Coil, Neodymium Compression Drive
Enclosure	Cast aluminum front baffles and HF waveguide, Finnish birch plywood; black DuraFlex™ finish, integral recessed handles
Inter-enclosure Angle	0, 0.5, 0.75, 1, 1.5, 2, 2.5, 3, 4, 5, 7.5, 10, 12.5
Dimensions (H x W x D)	280 mm x 911 mm x 402 mm 11 in x 35.9 in x 15.8 in
Net Weight (each)	40 kg (88 lbs)