

Specifications

Frequency Range (-10dB)	53 Hz - 20 kHz
Frequency Response (± 3 dB)	65 Hz – 20 kHz
System Power Rating	700 W (AES rated) 375 W / 750 W / 1500 W (Continuous/Program/Peak) (IEC rated)
Impedance	8 ohms
Coverage Pattern	/26: 120° x 60°/95: 90° x 50°
Dimensions (H x W x D)	679.5 x 237.5 x 254.0 mm (26.8 x 9.4 x 10.0 in)
Net Weight (each)	18.6 kg (40.9 lb)
Crossover Modes	Passive
Maximum SPL (1m)	120 dB
System Sensitivity (1w @ 1m)	94 dB SPL
LF Driver	2 x JBL 228J, 205 mm (8 in) SFG™ driver with 64 mm (2.5 in) edge wound voice coil
Nominal LF Driver Impedance	8 Ohms
HF Driver	1 x 2408H-1 25 mm (1 in) exit compression driver, 38 mm (1.5 in) voice coil
Enclosure	12 mm and 15 mm exterior grade multi-ply hardwood plywood
Suspension Attachment	6 x M8 points; 1 top, 3 bottom, 2 rear. 4 x M8 rear for MultiMount® MM-120-BT.
Environmental	Mil-Std 810; IPx3 per IEC529. For higher environmental ratings, use WRC or WRX.