

Specifications

Frequency Range (-10dB)	37 Hz – 20 kHz
Frequency Response (± 3 dB)	43 Hz – 18 kHz
Coverage Pattern	/64: 60° x 40°/66: 60° x 60°/95: 90° x 50°/00: 100° x 100°/26: 120° x 60°
Crossover Modes	Bi-amp/Passive switchable
Passive Crossover Frequency	1.5 kHz
Transducer Power Rating (AES)	LF: 400 W (1600 W peak), 2 hrs 300 W (1200 W peak), 100 hrs HF: 40 W (160 W peak), 2 hrs
System Power Rating	Passive mode: 300 W (1200 W peak), 100 hrs
Maximum SPL (1m)	Bi-amp mode: LF: 122 dB HF: 131 dB
System Sensitivity (1w @ 1m)	Passive mode: 96 dB SPL
LF Driver	1 x JBL 262H-1 300 mm (12 in) driver with 50.8 mm (2 in) dual voice coil
Nominal Impedance	8 ohms
Sensitivity (1W @ 1m, within operational band)	97 dB SPL
HF Driver	JBL 2408H-1, 38 mm (1.5 in) exit compression driver, 38 mm (1.5 in) voice coil
Sensitivity	113 dB SPL
Waveguide	PT-H126HF-1

Enclosure	Trapezoidal with 15 degree side angles, 16 mm (5/8 in) exterior grade 11-ply birch plywood
Suspension Attachment	15 points (4 top, 4 bottom, 2 each side, 3 rear), M10 threaded hardware
Finish	Black DuraFlex™ finish. White available upon request.
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Input Connector	NL4 Neutrik Speakon® and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop-through.
Environmental	Mil-Std 810; IP-x3 per IEC529
Dimensions (H x W x D in vertical orientation)	713 x 371 x 458 mm(28.06 x 14.6 x 18.1 in)
Net Weight (each)	20.2 kg (45 lb)
Optional Accessories	M10 x 35 mm forged shoulder eyebolts with washers U-Bracket MTU-3
System Power Rating	Passive mode: 300 W (1200 W peak), 100 hrs (IEC rated)
Nominal LF Driver Impedance	8 ohms
Nominal HF Driver Impedance	8 ohms