

## Specifications

|  |  |
|--|--|
| Frequency Range (-10dB)                        | 35 Hz - 20 kHz   |
| Frequency Response ( $\pm 3$ dB)               | 41 Hz – 20 kHz   |
| Coverage Pattern                               | /64: 60° x 40°/66: 60° x 60°/95: 90° x 50° /26: 120° x 60°                                     |
| Directivity Factor (Q)                         | 14.5   |
| Directivity Index (DI)                         | 11.6 dB  |
| Crossover Modes                                | Bi-amp/Passive switchable  |
| Passive Crossover Frequency                    | 2 kHz  |
| Transducer Power Rating (AES)                  | LF: 500 W (2000 W peak), 2 hrs<br>350 W (1400 W peak), 100 hrs<br>HF: 40 W (160 W peak), 2 hrs |
| System Power Rating                            | Passive mode: 350 W (1400 W peak), 100 hrs   |
| Maximum SPL (1m)                               | Bi-amp mode: LF: 125 dB-SPL cont avg<br>HF: 131 dB-SPL cont avg.                               |
| System Sensitivity (1w @ 1m)                   | Passive mode: 98 dB SPL  |
| LF Driver                                      | 1 x JBL 265H-1 380 mm (15 in) driver with 50.8 mm (2 in) dual voice coil                       |
| Nominal Impedance                              | 8 ohms   |
| Sensitivity (1W @ 1m, within operational band) | 99 dB SPL  |
| ... ..   | JBL 2408H-1, 38 mm (1.5 in) exit compression driver, 38 mm (1.5 in) voice                      |

|  |  |
|--|--|
| Sensitivity                                    | 115 dB SPL   |
| Waveguide                                      | PT-H66HF-1   |
| Enclosure                                      | Trapezoidal with 15 degree side angles, 16 mm (5/8 in) exterior grade 11-ply birch plywood   |
| Suspension Attachment                          | 15 points (4 top, 4 bottom, 2 each side, 3 rear), M10 threaded hardware  |
| Finish   | Black DuraFlex™ finish. White available upon request.  |
| Grille   | Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.   |
| Input Connector                                | NL4 Neutrik Speakon® and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop-through. |
| Environmental                                  | Mil-Std 810; IP-x3 per IEC529.   |
| Dimensions (H x W x D in vertical orientation) | 783 x 422 x 504 mm(30.8 x 16.6 x 19.85 in)   |
| Net Weight (each)                              | 25.0 kg (55 lb)  |
| Optional Accessories                           | M10 x 35 mm forged shoulder eyebolts with washers U-Bracket MTU-1  |
| System Power Rating                            | Passive mode: 350 W (1400 W peak), 100 hrs (IEC rated)   |
| Nominal LF Driver Impedance                    | 8 ohms   |
| Nominal HF Driver Impedance                    | 8 ohms   |