

## Specifications

Frequency Range (-10dB)	34 Hz - 20 kHz
Frequency Response ( $\pm 3$ dB)	40 Hz - 18 kHz
Coverage	/64: 60° x 40°/66: 60° x 60° /95: 90° x 50° /26: 120° x 60°
LF Driver	1 x JBL 2265H 380 mm (15 in) Differential Drive® driver with 75 mm (3 in) dual voice coil
HF Driver	JBL 2432H, 38 mm (1.5 in) exit compression driver, 75 mm (3 in) voice coil
System Type	15" Two - Way, High Power, Full - Range
Dimensions (H x W x D)	781 x 420 x 503 mm (30.8 x 16.5 x 19.8 in)
Net Weight (each)	27.2 kg (60 lb)
Crossover Modes	Bi-amp/Passive switchable
Passive Crossover Frequency	1.8 kHz
Transducer Power Rating (AES)	LF: 1000 W (4000 W peak), 2 hr750 W (3000 W peak), 100 hrsHF: 100 W (400 W peak), 2 hrs
System Power Rating	Passive mode: 600 W (2400 W peak), 100 hrs
Maximum SPL (1m)	Bi-amp mode:LF: 128 dB-SPL cont avg (134 dB peak)HF: 135 dB-SPL cont avg (141 dB peak)Passive mode:124 dB-SPL cont avg (130 dB peak)
System Sensitivity (1w @ 1m)	Passive mode: 96 dB SPL
Nominal Impedance	8 ohms
System Power Rating	Passive mode: 600 W (2400 W peak), 100 hrs (IEC rated)

Nominal LF Driver Impedance	8 ohms
Nominal HF Driver Impedance	8 ohms
Enclosure	Trapezoidal with 15 degree side angles, 16 mm (5/8 in) exterior grade 11-ply Finnish birch plywood
Suspension Attachment	15 points (4 top, 4 bottom, 2 each side, 3 rear), M10 threaded hardware
Environmental	Mil-Std 810; IP-x3 per IEC529.