

Specifications

Frequency Range (-10dB)	30 Hz – 1 kHz
Frequency Response (± 3 dB)	40 Hz – 1 kHz
Input Modes	Drivers Parallel / Drivers Discrete
Transducer Power Rating (AES)	1000 W (4000 W peak), 2 hrs
System Power Rating	600 W (2400 W peak), 100 hrs
Maximum SPL (1m)	30 Hz – 100 Hz: 133 dB-SPL cont avg (139 dB peak) 100 Hz – 500 Hz: 133 dB-SPL cont avg (139 dB peak)
System Sensitivity	30 Hz – 100 Hz: 103 dB 100 Hz – 500 Hz: 103 dB
Nominal Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode
LF Driver	2 x JBL 2042H 460 mm (18 in) drivers with 75 mm (3 in) voice coil
Nominal LF Driver Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode
Enclosure	Rectangular cabinet, 16 mm (5/8 in) exterior grade 11-ply Finnish birch plywood
Suspension Attachment	12 points (3 top, 3 bottom, 3 each side, 2 rear), M10 threaded hardware
Environmental	Mil-Std 810; IP-x3 per IEC529.
Net Weight (each)	143 lbs. (64.9 kgs)