

Specifications

Frequency Range (-10dB)	32 Hz - 1 kHz
Frequency Response (± 3 dB)	38 Hz - 1 kHz
Transducer Power Rating (AES)	1600 W (6400 W peak), 2 hrs
Input Modes	Drivers Parallel / Drivers Discrete
System Power Rating	1350 W (5400 W peak), 100 hrs.
Maximum SPL (1m)	35 Hz - 400 Hz: 132 dB-SPL cont avg (138 dB peak)
System Sensitivity	35 Hz - 400 Hz: 100 dB-SPL, 1W (2.0V) @ 1m
Nominal Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode
LF Driver	2 x 2265H-1, 380 mm (15 in) dia., 75 mm (3 in) Dual Coil Dual Gap neodymium Differential Drive® drivers
Enclosure	Rectangular cabinet, 16 mm (5/8 in) exterior grade 11-ply birch plywood
Suspension Attachment	16 points (4 top, 4 bottom, 4 each side), M10 threaded hardware
Finish	Black DuraFlex™ finish. White available upon request.
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Input Connector	NL4 Neutrik Speakon® and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop-through.
Environmental	Mil-Std 810; IP-x3 per IEC529.
Dimensions (H x W x D in vertical orientation)	965 x 419 x 597 mm (38.0 x 16.5 x 23.5 in)

Net Weight (each)	36.7 kg (81.0 lb)
Optional Accessories	M10 x 35 mm forged shoulder eyebolts with washers
Nominal LF Driver Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode