

Specifications

Frequency Range (-10dB)	28 Hz – 1 kHz
Frequency Response (± 3 dB)	35 Hz – 1 kHz
Input Modes	Drivers Parallel / Drivers Discrete
Transducer Power Rating (AES)	2400 W (9600 W peak), 2 hrs
System Power Rating	1600 W (6400 W peak), 100 hrs
Maximum SPL (1m)	30 Hz – 100 Hz: 136 dB-SPL cont avg (142 dB peak) 100 Hz – 500 Hz: 136 dB-SPL cont avg (142 dB peak)
System Sensitivity (1w @ 1m)	30 Hz – 100 Hz: 102 dB 100 Hz – 500 Hz: 102 dB
Nominal Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode
LF Driver	2 x JBL 2242H 460 mm (18 in) SVG™ drivers with 100 mm (4 in) voice coil
Nominal LF Driver Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete-drive mode
Enclosure	Rectangular cabinet, 16 mm (5/8 in) exterior grade 11-ply Finnish birch plywood
Suspension Attachment	12 points (3 top, 3 bottom, 3 each side, 2 rear), M10 threaded hardware
Environmental	Mil-Std 810; IP-x3 per IEC529.
Net Weight (each)	161 lbs. (73 kgs)