

## Specifications

Frequency Range (-10dB)	22 Hz - 1 kHz
Frequency Response ( $\pm 3$ dB)	34 Hz - 1 kHz
Transducer Power Rating (AES)	2000 W (8000 W peak), 2 hrs
System Power Rating	1200 W (4800 W peak), 100 hrs.
Maximum SPL (1m)	25 Hz - 200 Hz: 129 dB-SPL cont avg (135 dB peak)
System Sensitivity	25 Hz - 200 Hz: 96 dB-SPL, 1W (2.83V) @ 1m
Nominal Impedance	8 ohms
LF Driver	1 x 2269H, 460 mm (18 in) dia., 100 mm (4 in) Dual Coil Dual Gap neodymium Differential Drive® VGC™ driver
Enclosure	Rectangular cabinet, 16 mm (5/8 in) exterior grade 11-ply birch plywood
Suspension Attachment	16 points (4 top, 4 bottom, 4 each side) M10 threaded hardware
Finish	Black DuraFlex™ finish. White available upon request.
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Input Connector	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Environmental	Mil-Std 810; IP-x3 per IEC529.
Dimensions (H x W x D in vertical orientation)	546 x 560 x 815 mm(21.5 x 22.0 x 32.1 in)
Net Weight (each)	42.9 kg (94.5 lb)
Optional Accessories	M10 x 35 mm forged shoulder eyebolts with washers.
Nominal LF Driver Impedance	8 ohms