

Specifications

System Format	Extremely Wide Angle Coverage Dual 8" 2-Way Loudspeaker System
Frequency Range (-10dB)	71 Hz - 20 kHz
Frequency Response (± 3 dB)	96 Hz - 19 kHz
Coverage Pattern	160° x 60°
Maximum SPL (1m)	129 dB
System Nominal Impedance	8 Ohms
Long-Term System Power Rating	450W (1800W Peak)
System Power Rating	850W/1700W/3400W Continuous/Program/Peak
Crossover	1.5 kHz
LF Driver	2 x JBL 228J, 205 mm (8 in) SFG™ driver with 64 mm (2.5 in) edge wound voice coil
HF Driver	2 x 2408H-1 25 mm (1 in) exit compression driver, 38 mm (1.5 in) voice coil
High-Frequency Waveguide	Crossfired Waveguide
Finish	Black DuraFlex™ finish. White (-WH) available upon request
Dimensions (w x h x d)	811.28 x 259.59 x 300.74 mm (31.94 x 10.22 x 11.84 in)
Net Weight (each)	18.6 kg (40.9 lb)
Crossover Modes	Passive
System Sensitivity (1w @ 1m)	94 dB SPL

Nominal LF Driver Impedance	8 Ohms
Transformer Taps	70V: 110W, 55W, *28W 100V: 110W & 55W
Enclosure	12 mm and 15 mm exterior grade multi-ply hardwood plywood
Suspension Attachment	4 x M10 (1 x M10 points, one top, one bottom, plus 1 x M10 point on each side panel.) 4 x M8 rear for MultiMount® MM-120-BT
Environmental	Mil-Std 810; IPx3 per IEC529. For higher environmental ratings, use WRC or WRX.