

Specifications

Frequency Range (-10dB)	200 Hz to 18 kHz
Frequency Response (± 3 dB)	240 Hz to 16 kHz
Coverage Pattern	/43: 40° x 30°/64: 60° x 40°/66: 60° x 60°/95: 90° x 50°
Crossover Modes	Bi-amp / Passive switchable
Passive Crossover	6th order (36 dB / oct) Linkwitz-Riley HP & LP, 1.7 kHz
Transducer Power Rating (AES)	MF: 350 W (1400 W peak), 100 hrs HF: 75 W (300 W peak), 2 hrs (AES rated)
System Power Rating	Passive Mode: 300 W (1200 W peak), 100 hrs. (IEC rated)
Maximum SPL (1m)	"Bi-amp mode: MF: 135 dB-SPL cont avg (141 dB peak) HF: 135 dB-SPL cont avg (141 dB peak) Passive mode: 135 dB-SPL cont avg (141 dB peak)"
System Sensitivity (1w @ 1m)	Passive Mode: 110 dB SPL
MF Driver	CMCD-82H cone mid-range compression driver with integral 200 mm (8 in) diameter Neodymium Differential Drive NDD™ dual voice coil driver
HF Driver	2432H, 38 mm (1.5 in) exit compression driver with 75 mm (3 in) voice coil
Nominal Impedance	8 ohms
Enclosure	Trapezoidal with 15 degree side angles, 16 mm (.625 in) exterior grade 11-ply Finnish birch plywood
Suspension Attachment	20 points (5 top, 5 bottom, 4 each side, 2 rear), M10 threaded hardware (eyebolts NOT included, see optional accessories).
Finish	Black DuraFlex™ finish. White (-WH) available upon request.

Optional Weather Resistant Versions	WRC for outdoor placement where the loudspeaker will be sheltered from direct exposure to the elements. WRX for direct exposure or extreme environments, such as tropical or beach, or in areas with salt air, extreme high humidity or rapid changes in temperature.
Grille	Powder coated 14 gauge perforated steel, zinc-phosphate dipped, foam backing (grille cloth backing on white units)
Input Connectors	Neutrik Speakon® NL4, plus CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop through.
Environmental	Mil-Std 810; IP-x3 per IEC529. For higher environmental ratings, use WRC or WRX.
Dimensions (H x W x D in vertical orientation)	991 x 673 x 897 mm (39.0 x 26.5 x 35.3 in)
Net Weight (each)	58.8 kg (130 lb)
Optional Accessories	229-00009-01 kit of three M10 x 35 mm forged shoulder steel eyebolts
Nominal LF Driver Impedance	8 ohms
Nominal MF Driver Impedance	8 ohms