

Specifications

Frequency Range (-10dB)	80 Hz to 18 kHz
Frequency Response (± 3 dB)	90 Hz to 16 kHz
Coverage Pattern	/43: 40° x 30°/64: 60° x 40°/66: 60° x 60°/95: 90° x 50°
Crossover Modes	Bi-amp / Passive switchable
Passive Crossover	6th order (36 dB/oct) Linkwitz-Riley HP & LP, 850 Hz
Transducer Power Rating (AES)	LF: 400 W (1600 W peak), 2 hrs. 300 W (1200 W peak), 100 hrs HF: 75 W (300 W peak), 2 hrs
System Power Rating	Passive Mode: 300 W (1200 W peak), 100 hrs
Maximum SPL (1m)	LF: 137 dB-SPL HF: 135 dB SPL (141 dB peak)Passive Mode: 134 dB SPL (140 dB peak)
System Sensitivity	Passive Mode: 107 dB-SPL
LF Driver	M222-8A 300 mm (12 in) driver with 75 mm (3 in) voice coil
HF Driver	2453H, 38 mm (1.5 in) exit compression driver with 100 mm (4 in) voice coil
Nominal Impedance	8 ohms
Enclosure	Trapezoidal with 12.5 degree side angles, 16 mm (5/8 in) exterior
Suspension Attachment	20 points (5 top, 5 bottom, 4 each side, 2 rear), M10 threaded hardware
Finish	Black DuraFlex™ finish. White (-WH) available upon request.
Optional Weather Resistant Versions	WRC for outdoor placement where the loudspeaker will be sheltered from direct exposure to the elements.
Grille	Powder coated 14 gauge perforated steel, zinc-phosphate dipped, foam

Input Connectors	Neutrik Speakon® NL4, plus CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop through.
Environmental Specifications:	Mil-Std 810; IP-x3 per IEC529.
Dimensions (H x W x D in vertical orientation)	991 x 673 x 897 mm
Net Weight (each)	69 kg (152 lb)
Optional Accessories	229-00009-01 kit of three M10 x 35 mm forged shoulder steel eyebolts.
Nominal LF Driver Impedance	8 ohms
Nominal HF Driver Impedance	8 ohms