

## Display

<b>Panel Technology</b>	Direct View LED	<b>Aspect Ratio</b>
<b>Native Resolution</b>	1920x1080	<b>Module Resolution</b>
<b>Pixel Configuration</b>	3-1 SMD (Black)	<b>Pixel Pitch</b>
<b>Brightness (typical)</b>	1000 cd/m <sup>2</sup>	<b>Brightness (maximum)</b>
<b>Contrast Ratio (typical)</b>	7000:1	<b>Viewing Angle (typical)</b>
<b>Refresh Rate</b>	Up to 3840 Hz	<b>Active Screen Area</b>
<b>Orientation</b>	Landscape	<b>Dimming Capability</b>
<b>Color Processing</b>	Up to 18 bit	<b>Displayable Colors</b>
<b>Color Temperature (Max) (°K)</b>	3000	<b>Color Temperature (Typical) (°K)</b>
<b>Color Temperature (Min) (°K)</b>	9500	<b>Gamma (Max)</b>
<b>Gamma (Typical)</b>	2.8	<b>Gamma (Min)</b>
<b>Lifetime</b>	100,000 hours	

## Signal Compatibility/Connectivity

<b>External Control</b>	1 x GenLock; 1 x LAN	<b>Input Terminals</b> Digital: 1 x 3G SDI; 1 x DVI-D; 1 x HDM External Control: RS232 / USB
-------------------------	----------------------	--

---

## Power Consumption (typical)

<b>On</b>	2560Watts	<b>Power Consumption (max)</b>
-----------	-----------	--------------------------------

---

Without stand:  
188.8 x 106.4 x 1.1 in. / 4800 x 2700 x 29 mm

Net Weight (without stand):  
665.6 lbs. / 300.8 kg.

Servicability:

Front Service

IP Level:

IP20

Certifications:

- UL
- VCCI (Class A)
- S-TUV
- HDMI
- FCC Class A
- >
- RoHS



## Environmental Conditions

<b>Operating Temperature</b>	-4° to 104°F / -20° to 40°C	<b>Operating Humidity</b>
<b>Storage Temperature</b>	-4° to 113°F / -20° to 45°C	<b>Storage Humidity</b>
<b>Environment</b>	Indoor	

## Limited Warranty (parts & labor)

2 years

## Accessories

### Included

- LED Controller
- Overframe Kit (8x8)
- Pixel Card Removal Tool
- Starter Bar; Spare Parts Kit
- Wall mount (8x8)

### Optional