



NEXT LEVEL HOME THEATER

The Klipsch Reference Cinema System 5.0.4 with Dolby Atmos combines Reference Series acoustics with Dolby Atmos technology to deliver an immersive, multidimensional experience you won't find anywhere else.

SOUND ALL AROUND

Featuring four satellite speakers outfitted with Dolby Atmos technology, the Klipsch Reference Cinema System delivers height effects from the front AND the back for a best-in-class Dolby Atmos experience.

MINIMAL FOOTPRINT

Connecting easily to your A/V receiver, this compact system is perfectly tuned for maximum impact.

REACH NEW HEIGHTS

Ideal for movies, music, and gaming, Dolby Atmos brings sound to life from all directions, including overhead, to fill the room with astonishing clarity, detail and depth.

LEGENDARY TECHNOLOGY

90° X 90° TRACTRIX® HORN

Our exclusive Tractrix horn technology delivers an impressive high-end response and greater extension, enhanced imaging and powerful dynamics.

REFERENCE-GRADE TWEETERS

Aluminum tweeters with Linear Travel Suspension (LTS) minimize distortion for enhanced, detailed sound and have long been a hallmark of our Reference Series product lines.

SPUN COPPER IMG WOOFERS

Injection Molded Graphite (IMG) woofers are exceptionally light and extremely rigid - providing remarkable low frequency response, with minimal cone breakup or distortion.

DUAL PORT DESIGN

The dual port design provides improved cabinet tuning and low frequency response for impactful bass performance from every single component of the Reference Cinema System.

NEXT-GEN COMPATIBLE

Dolby Atmos is the gold standard in premium, cutting-edge home theater sound. The [Klipsch](#) Reference 5.0.4 Cinema Systems offers an all-in-one speaker setup to future proof your listening experience for all new movies, music, and games.

SPECIFICATIONS - SATELLITE

FREQUENCY RESPONSE: 90Hz-20kHz (+/- 3dB)

SENSITIVITY: 92 dB @ 2.83V / 1M

POWER HANDLING (CONT/PEAK): 75W/300W

NOMINAL IMPEDANCE: 8 ohms compatible

CROSSOVER FREQUENCY: 2000Hz

HIGH-FREQUENCY DRIVER: 1" Aluminum LTS Tweeter Mated to a 90x90 Tractrix® Horn

LOW-FREQUENCY DRIVER: 5.25" Spun-Copper IMG Woofer INPUTS Single Gold Plated Binding Posts

ENCLOSURE TYPE: Bass-Reflex via dual front-firing ports

HEIGHT: 13.47" (342.1 mm)

WIDTH: 6.47" (164.3 mm)

DEPTH: 7.45" (189.2 mm)

WEIGHT: 8.2 lb (3.72 kg)

MOUNTING: 1/4" x 20 Threaded Insert

SPECIFICATIONS - CENTER

FREQUENCY RESPONSE: 80Hz-20kHz (+/- 3dB)

SENSITIVITY: 91 dB @ 2.83V/1M

POWER HANDLING (CONT/PEAK): 75W/300W

NOMINAL IMPEDANCE: 8 ohms compatible

CROSSOVER FREQUENCY: 1800Hz

HIGH-FREQUENCY DRIVER: 1" Aluminum LTS Tweeter Mated to a 90x90 Tractrix® Horn

LOW-FREQUENCY DRIVER: Dual 4" Spun-Copper IMG Woofers

INPUTS: Single Gold Plated Binding Posts

ENCLOSURE TYPE: Bass-Reflex via dual front-firing ports

HEIGHT: 5.16" (131.1 mm)

WIDTH: 17.60" (447.0 mm)

DEPTH: 6.07" (154.2 mm)

WEIGHT: 7.4 lb (3.36 kg)

MOUNTING: Dual 1/4" x 20 Threaded Insert

SPECIFICATIONS - HEIGHT CHANNEL

FREQUENCY RESPONSE: Conforms to Dolby Atmos Specifications

SENSITIVITY:Conforms to Dolby Atmos Specifications

POWER HANDLING (CONT. / PEAK): 40W/160W

NOMINAL IMPEDANCE: 8 ohms compatible

DRIVER:4" Polyfiber Woofer

ENCLOSURE TYPE:Acoustic Suspension

INPUTS: Single Gold Plated Binding Posts