

Specifications

Technical Data

Speaker Type: Active Bassreflex Subwoofer

Acoustical Data

Frequency Response [- 6 dB]: 40 Hz – (user frequency LPF)

Frequency Response [- 10 dB]: 36 Hz – (user frequency LPF)

Max SPL: 134 dB

LF: 1x 15"

Voice Coil LF: 4"

Directivity: Omnidirectional

Amplifier

Amp Technology: Digipro® G3

Amp Class: Class D

RMS Power: 900 W

Peak Power: 1800 W

Cooling: Convection

Processor

Controller: DSP 32 bit

AD/DA Converter: 24 bit/96 KHz

Limiter: RMS, Peak, Thermal

Input

Signal Input:

1xXLR balanced

1xRJ45 LINK (RDNet)

Signal Output:

1x XLR balanced

1xRJ45 LINK (RDNet)

Power Socket:

1xPowerCON TRUE1 IN

1xPowerCON TRUE1 OUT

Controls:

1x Input Sensitivity Rotary Encoder

1x X-Over Selection Encoder

1x Delay Selection Encoder

1x Polarity Selection Switch

1x X-Out Mode Selection Switch

1x On LED

1x Status LED

1x Signal LED

1x Limiter LED

3x RDNet Status LED

Mechanics

Housing:

Multiplex plywood

Polyurea painted

Pole Mount: 1x M20 on Top, 1x M20 on Right Side

Handles:

1x Side

Aluminium

Rigging Points: 16x M10

Width: 650 mm (25.6 in)

Height: 420 mm (16.5 in)

Depth: 550 mm (21.7 in)

Weight: 32.8 kg (72.3 lbs)