

Specifications

- Technical Data
 - Speaker Type: 2-Way Active Wedge Monitor
 - Usable Bandwidth [- 10 dB]: 58 - 15,000 Hz
 - Frequency Response [- 6 dB]: 68 - 14,000 Hz
 - Max SPL: 126 dB
 - HF: 4x 4" - 1" v.c. Neodymium
 - LF: 1x 10" - 2.5" v.c.
 - Horizontal Directivity: Dependent on Focus Preset
 - Vertical Directivity: Dependent on Focus Preset
 - Amplifier: 400 W RMS Class D Digipro® G3
 - Cooling: Convection
 - Power Supply: Auto-range SMPS
 - Controller: DSP 28/56 bit
 - Converter AD/DA: 24 bit/48 kHz
 - Limiter: Peak, RMS, Thermal
 - Processing (filters): Linear Phase FIR Filters
 - Signal Input: 1x XLR female, 1x RJ45 Link (RDNet) , 1 x USB (Data Service)
 - Signal Output: 1xXLR male, 1x RJ45 Link (RDNet)
 - Power Socket:
 - 1x PowerCON TRUE1 In
 - 1xPowerCON TRUE1 Out
 - Controls:
 - 1x Rotary Encoder (8 presets)
 - 1 x Input Sensitivity Encoder
 - 1xMic /line switch
 - 1x On LED
 - 1x Status -LED
 - 1x Signal LED
 - 1x Limiter LED
 - Housing: Wooden cabinet, Polyurea painting
 - Handles: 1 on left side
 - Width: 450 mm (17.71 in)
 - Height: 165 mm (6.49 in)
 - Depth: 480 mm (18.89 in)
 - Weight: 13.7 kg (30.20 lbs)