

Cabinet

Area	0.2025 m ²
Cabinet Flatness	0.1 mm
Cabinet Material	Magnalium
Dimensions (W × H × D)	600 mm × 337.5 mm × 50.9 mm (23.62" × 13.29" × 2.00")
Lamp Board Housing	With housing
Maintenance Method	Front maintenance for all components
Modules Component	2 × 4
Pixel Configuration	SMD Triad LED
Pixel Density	409600 dots/m ²
Pixel Pitch	1.5625 mm
Pixel Pitch Category	P1.5
Protection Level	Front protection level IP60
Resolution	384 × 216
	5.4 Kg (11.9 lb)

Display

Brightness Uniformity	≥ 97%
Color Temperature	3000 K to 10000 K adjustable
Color Uniformity	≤ ± 0.003Cx, Cy
Contrast Ratio	≥ 5000:1
Viewing Angle	Horizontal 160°, vertical 160°
White Balance	800 cd/m ²
Brightness	

Processing Performance

Display Color 281 trillion

Driving Method Constant current driving

Frame Frequency 60 Hz

Grey Level Up to 16 bit

Refresh Rate Up to 3840 Hz

Working Environment

Storage Humidity 10%~80%RH

Storage Temperature -20~60 °C

Working Humidity 10%~80%RH

Working Temperature -10-40 °C
