

## Specifications:

### Printing:

- Print technology: Laser
- Printing: Mono printing
- Duplex printing: Yes
- Maximum resolution: 1200 x 1200 DPI
- Print speed (black, normal quality, A4/US Letter): 55 ppm
- Warm-up time: 65 s
- Warm-up time (from sleep mode): 11 s
- Time to first page (black, normal): 7.5 s
- Time to first page (colour, normal): 7.5 s

### Copying:

- Copying: Mono copying
- Duplex copying: Yes
- Maximum copy resolution: 600 x 600 DPI
- Copy speed (black, normal quality, A4): 55 cpm
- Time to first copy (black, normal): 5.8 s
- Maximum number of copies: 999 copies
- Copier resize: 25 - 400%
- N-in-1 copy function: Yes
- Book copy function: Yes
- ID-card copy function: Yes
- Background adjustment function: Yes
- Edge erase function: Yes

### Scanning:

- Scanning: Color scanning
- Duplex scanning: Yes
- Scan to: E-mail,FTP,File,USB
- Scan speed (colour): 55 ppm
- Scan speed (black): 58 ppm
- Image formats supported: JPG,TIF
- Document formats supported: PDF,XPS
- Scan drivers: TWAIN,WIA

### Fax:

- Faxing: No

### Features:

- Maximum duty cycle: 300000 pages per month
- Number of print cartridges: 1
- Page description languages: HP-GL,PCL 5e,PCL 6,PostScript 3
- Digital sender: Yes
- Input & output capacity:
- Total number of input trays: 2
- Total input capacity: 700 sheets
- Total output capacity: 400 sheets
- Paper input type: Paper tray
- Auto document feeder (ADF): Yes
- Auto document feeder (ADF) input capacity: 100 sheets

### Paper handling:

- Maximum ISO A-series paper size: A4

### Ports & interfaces:

- Direct printing: No

#### Ports & interfaces:

- USB port: Yes
- Standard interfaces: Ethernet,USB 3.2 Gen 1 (3.1 Gen 1)
- USB 3.2 Gen 1 (3.1 Gen 1) ports quantity- 1
- Optional connectivity- Wireless LAN

#### Network:

- Ethernet LAN: Yes
  - Cabling technology: 10/100/1000Base-T(X)
  - Ethernet LAN data rates: 10,100,1000 Mbit/s
  - Near Field Communication (NFC): Yes
  - Security algorithms: 256-bit AES,FIPS 140-2,HTTPS,IPPS,IPSec,SNMPv3,SSL/TLS
- Supported network protocols (IPv4)TCP/IP:HTTP/HTTPS, InternetPrintingProtocol, LPR/LPD, RawSocketPrinting/Port9100, IPv4/IPv6, WSD, LDAP, Bonjour/Air Print, FTP
- Management protocols: Apple Bonjour, Email alerts, Xerox CentreWare Web, Xerox Embedded Web Server
  - Mobile printing technologies: Apple AirPrint,Google Cloud Print,Mopria Print Service,Xerox PrintBack

#### Performance:

- Internal memory: 4096 MB
- Maximum internal memory: 4096 MB
- Internal storage capacity: 250 GB
- Built-in processor: Yes
- Processor frequency: 1050 MHz
- Processor cores: 2
- CompatibilityVersa: Link B605/B615

#### Design:

- Product colour: Blue,White
- Market positioning: Business
- Built-in display: Yes

#### Power:

- Energy Star certified: Yes
- Power consumption (average operating): 820 W
- Power consumption (standby): 90 W
- Power consumption (sleep): 0.9 W

#### System requirements:

- Windows operating systems supported: Windows 10,Windows 10 Education,Windows 10 Education x64,Windows 10 Enterprise,Windows 10 Enterprise x64,Windows 10 Home,Windows 10 Home x64,Windows 10 Pro,Windows 10 Pro x64,Windows 7,Windows 7 Enterprise,Windows 7 Enterprise x64,Windows 7 Home Basic,Windows 7 Home Basic x64,Windows 7 Home Premium,Windows 7 Home Premium x64,Windows 7 Professional,Windows 7 Professional x64,Windows 7 Starter,Windows 7 Starter x64,Windows 7 Ultimate,Windows 7 Ultimate x64,Windows 8,Windows 8 Enterprise,Windows 8 Enterprise x64,Windows 8 Pro,Windows 8 Pro x64,Windows 8 x64,Windows 8.1,Windows 8.1 Enterprise,Windows 8.1 Enterprise x64,Windows 8.1 Pro,Windows 8.1 Pro x64,Windows 8.1 x64
- Mac operating systems supported: Mac OS X 10.10 Yosemite,Mac OS X 10.11 El Capitan,Mac OS X 10.12 Sierra

Linux operating systems supportedFedora 24,openSUSE 13.2

Server operating systems supportedWindows 2000 Server,Windows Server 2003,Windows Server 2008,Windows Server 2008 R2,Windows Server 2012

- Other operating systems supported: HP-UX 11.31,IBM AIX 7.2,Solaris 11

#### Operational conditions:

- Operating relative humidity (H-H): 10 - 85%
- Storage temperature (T-T): -20 - 40 °C
- Operating temperature (T-T): 10 - 32 °C
- Storage relative humidity (H-H): 10 - 95%

#### Packaging data:

- Package width: 594 mm
- Package depth: 655 mm
- Package height: 789 mm
- Package weight: 38 kg

Packaging content:

- Manual: Yes
- Power cord included: Yes