

Product Description	Xerox VersaLink B615V_XL - multifunction printer (B/W)
Device Type	Fax / copier / printer / scanner
Fax Type	Plain paper
Printing Technology	LED (monochrome)
Max Copying Resolution	Up to 600 x 600 dpi
Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Scanning	600 x 600 dpi
Display	7"
Original Type	Sheets
Document Feeder Capacity	100 sheets
Media Size	76 x 127 mm (min)
Media Type	Envelopes, plain paper, labels, recycled paper, bond paper, card stock, punched paper, preprinted paper
Bypass Feeder Capacity	150 sheets
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
PC Connection Availability	Yes
PC Connection	Gigabit LAN, USB host, NFC, USB 3.0
AirPrint Enabled	Yes
Power	AC 230 V (50/60Hz)
Environmental Standards	ENERGY STAR Qualified

Detailed Specification

General

Device Type	Fax / copier / printer / scanner
Fax Type	Plain paper
Printing Technology	LED - monochrome
Display Diagonal Size	7"

Colour Support	Colour
Display Features	Touch screen
PC Connection Availability	Yes
PC Connection	Gigabit LAN, USB host, NFC, USB 3.0
AirPrint Enabled	Yes

Memory

Standard Memory	2 GB
Hard Disk Drive	250 GB

Copying

Max Copying Resolution	Up to 600 x 600 dpi
Max Document Enlargement	400%
Max Document Reduction	25%
Maximum Copies	999
Automatic Duplexing	Yes

Printing

Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Printer Drivers / Emulations	PCL 5e, PCL 6, PostScript 3, PDF, TIFF, HPGL, XPS, JPEG
Automatic Duplexing	Yes

Scanning

Automatic Duplexing	Yes
Optical Resolution	600 x 600 dpi
Grayscale Depth	8-bit
Colour Depth	24-bit

Document & Media Handling

Original Type	Sheets
Document Feeder Capacity	100 sheets
Min Media Size	76 x 127 mm

Min Media Weight	60 g/m ²
Max Media Weight	220 g/m ²
Supported Media Type	Envelopes, plain paper, labels, recycled paper, bond paper, card stock, punched paper, preprinted paper
Bypass Feeder Capacity	150 sheets

Connections

Security Protocols & Features	Secure Print, SSL, TLS, Secure Fax, IP filtering, port blocking, AES-256, Secure Scan, Secure Email
-------------------------------	---

Power

Voltage Required	AC 230 V (50/60Hz)
------------------	--------------------

Environmental Standards

ENERGY STAR Certified	Yes
-----------------------	-----

Environmental Parameters

Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	15 - 85%