

# Technical Parameters

Notice: The parameters below are only for your reference.

<b>Build Volume</b>
200*200*200mm
<b>Molding Technology</b>
Fused Deposition Modeling
<b>Printing Filament</b>
PLA, ABS, TPU, Copper PLA, Wood, Carbon Fiber, etc.
<b>Machine Dimension</b>
358*375*420mm
<b>Shipping Dimension</b>
465*450*515mm
<b>Filament Diameter</b>
1.75mm
<b>Layer Thickness</b>
0.05-0.4mm
<b>File Format</b>
STL, Gcode, OBJ
<b>Print Speed</b>
≤200ms
<b>Nozzel Diameter</b>
0.4mm (accept 0.3 & 0.5mm)
<b>Max Extruder Temp</b>
260°C
<b>Max Hotbed Temp</b>
90°C
<b>Language</b>
English/Chinese

**Display Screen**

3.2 inches Full color touch screen

**Positioning Precision**

X/Y: 0.011mm Z: 0.0025mm

**Stepper Motors**

1.8°C step angle with 1/16 micro-stepping

**Power Supply**

DC 24V/15A/360W

**Shipping Weight**

18kg

**Work Mode**

Online or Offline(SD card/USB)

**Operating System**

Windows, MAC, Linux

**Special Function**

Filament break warning and power off resume