
GENERAL INFO

Type	TV
Year	2021
Brand	TCL
Model Series	P618
Model Number	65P618
Size	65" (inches)
Operating System	Android 9.0 Pie

DISPLAY

Screen Size Class	65" (inches)
Diagonal Size	64.53 in 163.9 cm 1639 mm 5.38 ft
Screen Width	56.24 in 142.8 cm 1428.48 mm 4.69 ft
Screen Height	31.63 in 80.4 cm 803.52 mm 2.64 ft
Display Bit Depth	10 bits (8 bits -
Frame Rate Control	Yes
Max Number of Colors	1073741824
Bits	30
Screen Aspect Ratio	16:9
Screen Resolution	3840 x 2160
Screen Pixel Pitch	0.372 mm
Screen Pixel Density	68 ppi
Screen-to-Body Ratio	93.58 %
Backlight Source	Direct LED
Screen Horizontal Viewing Angle	178 °
Screen Vertical Viewing Angle	178 °
Display Coating	Anti-glare/Matt

SIZE, WEIGHT, COLOR

Case Depth	3.35 in 8.5 cm 85 mm 0.28 ft
Case Weight	17.2 kg 38 lbs
Case Width with Stand	57.28 in 145.5 cm 1455 mm 4.77 ft
Case Height with Stand	35.39 in 89.9 cm 899 mm 2.95 ft
Case Depth with Stand	13.86 in 35.2 cm 352 mm 1.15 ft
Case Weight with Stand	17.3 kg 38 lbs
Case Color	Silver

HARDWARE

CPU Cores	2
TV Tuner	Terrestrial digit BS 110 Degree CS BS 4K 110 Degree CS
Built-in Camera	No
Network	LAN Wi-Fi 802.11a (IEEE 802.11b (IEEE 802.11g (IEEE 802.11n (IEEE 802.11n 5GHz 802.11ac (IEEE Wi-Fi Direct DLNA Bluetooth 5.0
Connectivity	1 x Ethernet R. 3 x HDMI 2.0 (C 1 x AV Compos 1 x 3.5 mm Au 1 x Optical Auc 1 x Satellite In 1 x USB 2.0 1 x Antenna (R 1 x USB 3.0

ERGONOMICS

Case Width	57.28 in 145.5 cm 1455 mm 4.77 ft
Case Height	33.19 in 84.3 cm 843 mm 2.77 ft
Vesa Mount Support	Yes
VESA Interface Standard Size	300 x 300
Removable VESA Stand	Yes
Height Adjustment	No
Landscape or Portrait Pivot Support	No
Left or Right Swivel Support	No
Forward and Backward Tilt Support	No

FREQUENCY AND INTERPOLATION

Vertical Digital Frequency	50 Hz / 60 Hz
Screen Interpolation Measurement Unit	NULL

POWER

220V	220 V - 240 V
AC Frequency	50 Hz - 60 Hz
Power Consumption in Sleep Mode	0.3 W
Average Power Consumption	150 W

ACCESSORIES

Extras	Remote contro
--------	---------------

CERTIFICATES AND STANDARDS

Licenses	RoHS
----------	------

USAGE AND STORAGE REQUIREMENTS

Safe Operating Temperature Level	5 °C - 35 °C 41 °F - 95 °F
Safe Operating Humidity Level	20 % - 80 %
Internal Storage Temperature	-15 °C - 45 °C 5 °F - 113 °F
Internal Storage Humidity	10 % - 90 %