

Shure PGA-Studio Specs

Type	PGA52: Dynamic (moving coil) PGA57: Dynamic (moving coil) PGA181: Electret Condenser
Frequency Response	PGA52: 50 Hz to 12 kHz PGA57: 70 Hz to 15 kHz PGA181: 50 Hz to 20 kHz
Polar Pattern	All Mics: Cardioid
Output Impedance	PGA52: 150 ohms PGA57: 150 ohms PGA181: 120 ohms
Sensitivity	PGA52: -55 dBV/Pa (1.75 mV) 1 Pa=94 dB SPL @ 1 kHz, open circuit voltage PGA57: -56 dBV/Pa (1.5 mV) 1 Pa=94 dB SPL @ 1 kHz, open circuit voltage PGA181: -38 dBV/Pa (12.7 mV), 1 Pa=94 dB SPL @ 1 kHz, open circuit voltage
Polarity	All Mics: Positive pressure on diaphragm produces positive voltage on pin 2 with respect to pin 3
Output Connector	All Mics: 3-pin XLR male
Cable Length	15' (4.6 m)
Power Requirements	PGA52: N/A PGA57: N/A PGA181: 48 VDC phantom power (4 mA)
Operating Temperature	All Mics: -20 to 165°F (-29 to 74°C)
Operating Humidity	All Mics: 0 to 95%
Dimensions	Not specified by manufacturer
Weight	PGA52: 16.01 oz (454 g) PGA57: 9.9 oz (280 g)

PGA181: 13.5 oz (383 g)

Packaging Info

Package Weight

9.65 lb

Box Dimensions (LxWxH)

22.6 x 13 x 4.3"
