

ZW350e Compact high brightness laser projector





- Bright WXGA laser projector 4000 lumens and IP6X certified
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- Compact for easy installation 1.1x zoom, 360degree and portrait projection
- External power supply More reliability, portability and energy efficiency

The ZW350e is one of Optoma's most compact and hassle-free WXGA DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4,000-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹



An added benefit, the ZW350e features an external power supply offering more reliability, portability and energy efficiency.

Specifications

Specifications	
EAN: 5055387666382, Colour: \	Nhite
JPC: 796435 44 612 3, Colour:	White
Display/image	
Display technology	DLPTM
Resolution	WXGA (1280x800)
Brightness	4,000 lumens
Contrast ratio	300,000:1
Contrast ratio - dynamic	2,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Displayable colours (millions)	1073.4
lorizontal scan rate	15 ~ 140Khz
/ertical scan rate	24 ~ 120Hz
Jniformity	75%
Screen size	0.51m ~ 7.62m (20" ~ 300") diagonal
Lamp info	0.0 mm + 7.02 m (20 + 600) diagonai
Light source type	Laser
_ASER life	
	30,000 hours
Optical Throw ratio	1.54:1 ~ 1.72:1
	1.54:1 ~ 1.72:1 1m - 10m
Projection distance (m)	
Zoom	1.1 Menual
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.00
Native offset	112%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	
Noise level (min)	27dB
Voise level (max)	34dB
PC compatibility	
	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	Full 3D
Security	
P rating	Security bar, Kensington Lock, Password protected interface IP6X
•	
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
	Einnish French German Greek Hungarian Indonesian Italian
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian
24/7 operation	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
360° operation	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
360° operation Operating conditions	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m
360° operation Dperating conditions Remote control	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style
360° operation Operating conditions Remote control Speaker count	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1
360° operation Operating conditions Remote control Speaker count Watts per speaker	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W
360° operation Operating conditions Remote control Speaker count Watts per speaker	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord
860° operation Operating conditions Remote control Speaker count Watts per speaker	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W
000° operation Operating conditions Remote control Speaker count Vatts per speaker	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery
060° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models Power	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes O''C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power supply Power consumption (standby)	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power Power consumption (standby) Power consumption (min)	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power Consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W
360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W
24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm Gross weight Net weight	Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. ¹ Based on the comparison of the 2023 Optoma mainstream laser projectors and its previous generation. ² Comparison of 2023 Optoma mainstream laser projectors. 08122023094313