

DMInteract®

From Visualization to Collaboration



DMInteract DM3MM-OD

P3mm High Resolution SMD
Technology Outdoor Dot LED
Video Wall Displays



BEST IN CLASS

DMINTERACT DM3MM-OD

**P3mm High Resolution SMD Technology
Outdoor Dot LED Video Wall Displays**

**Available Sizes:
100", 150", 180" And 200"**

PRODUCT OVERVIEW

The DMInteract P3mm High Resolution SMD Technology Outdoor Dot LED Video Wall Displays are designed for superior visual performance and durability. Featuring a fine P3mm pixel pitch and a high pixel density of 105625 pixels per square meter, the display delivers sharp, clear images. The module size of 320x160mm and cabinet size of 640x640mm, made from die-casting aluminum, ensure robust construction and easy installation. With a wide viewing angle of 140-160 degrees and exceptional brightness of $\geq 5000\text{cd}/\text{m}^2$, the display provides excellent visibility from various positions, even in direct sunlight. The high refresh rate of 3840Hz ensures smooth video playback, while energy-efficient operation (260-450W/ m^2 average, 950W/ m^2 max) and a life span of over 100,000 hours guarantee long-term reliability. Suitable for outdoor environments, the display performs optimally in a wide operating temperature range (-30°C to 65°C) and humidity levels (10% to 90%).



Specifications of the DMInteract DM3MM-OD Outdoor Dot LED Solution:

Brand Name:	DMInteract
Model Number:	DM3MM-OD
Pixel Pitch:	P3mm
Suitable For:	Outdoor
Module Size:	320x160mm
Module Resolution:	104x52 Pixels
Pixel Configuration:	RGB
LED Lamp:	SMD1415
Driving Method:	1/13scan
Pixel Density:	105625 Pixels/SQM
Refresh Rate:	3840Hz
Viewing Angle:	140-160 Degrees
Brightness:	≥5000cd/m²
Cabinet Size:	640x640mm

Specifications of the DMInteract DM3MM-OD Outdoor Dot LED Solution:

Cabinet Resolution:	208x208 Pixels
Cabinet Material:	Die-Casting Aluminum
Average Consumption:	260-450W/m²
Max. Consumption:	950 W/m²
Input Voltage:	AC220V-240V/50-60Hz
Operating Humidity:	10% ~ 90%
Operating Temperature:	-30°C~65°C
Life Span:	≥100,000 Hours
Cabinet Weight:	8kg/pc

Available Sizes Of The DMInteract DM3MM-IN Outdoor Dot LED Solution:

DMInteract 100" Outdoor P3mm Dot LED Display

Screen Size: 1.92(W) x 1.28(H)m = 2.46sqm

Diagonal Size: Around 100"

Refresh Rate: 3840Hz

Cabinet Quantity: 3 x 2 = 6 Units

DMInteract 150" Outdoor P3mm Dot LED Display

Screen Size: 3.2(W) x 1.92(H)m = 6.144sqm

Diagonal Size: Around 150"

Refresh Rate: 3840Hz

Cabinet Quantity: 5 x 3 = 15 Units

DMInteract 180" Outdoor P3mm Dot LED Display

Screen Size: 3.84(W) x 1.92(H)m = 7.37sqm

Diagonal Size: Around 180"

Refresh Rate: 3840Hz

Cabinet Quantity: 6 x 3 = 18 Units

DMInteract 200" Outdoor P3mm Dot LED Display

Screen Size: 4.48(W) x 2.56(H)m = 11.5sqm

Diagonal Size: Around 200"

Refresh Rate: 3840Hz

Cabinet Quantity: 7 x 4 = 28 Units



SPECIAL OFFER

ORDER NOW



 **DEALER ADDRESS:**

Showroom G-02, IT Plaza, Dubai Silicon Oasis, Dubai, United Arab Emirates

 **CANADA OFFICE:**

DMInteract Inc 801 Dundas Street East, Unit #D6, Mississauga, Ontario, L4Y 4G9

 **CONTACT NUMBER:**

+971-4-3360300 - (Dubai Office)

437-880-7712 - (Mississauga Office)

 **EMAIL ADDRESS:**

info@dminteract.com