

Specifications

Photo is representative

Eaton 5E2200UI

Eaton 5E Gen2 UPS USB IEC, 2200 VA, 1200 W, Input: C14, Outputs: (6) C13, Tower

General specifications

PRODUCT NAME	Eaton 5E Gen2 UPS
CATALOG NUMBER	5E2200UI
EAN	3553340704376
PRODUCT LENGTH/DEPTH	330 mm
PRODUCT HEIGHT	180 mm
PRODUCT WIDTH	133 mm
PRODUCT WEIGHT	9.82 kg
COMPLIANCES	CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC UKCA Cm Ukr IEC/EN 62040-3



Powering Business Worldwide

Product specifications

SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design
- HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

TOPOLOGY	Line-interactive
CONSTRUCTION TYPE	Free standing model
COLOR	Black
VA RATING	2200 VA
WATTAGE	1200 W
RACK MOUNTING KIT	No
PACKAGE CONTENTS	• (2) IEC-IEC output cables • Quick start • Safety instructions
SURGE PROTECTION	Yes
INTERNAL BYPASS	No
HOT SWAP POWER	No
AUTO SHUTDOWN FUNCTION	Yes
PRIMARY FREQUENCY - MAX	63 Hz
PRIMARY FREQUENCY - MIN	45 Hz
INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	45-63 Hz
RECEPTACLE	(6) C13
NUMBER OF OUTPUTS C13	6
VOLTAGE	230V
OUTPUT NOMINAL VOLTAGE	230V
FEED TYPE	1
VOLTAGE TYPE	AC

Resources

BROCHURES	eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf
CERTIFICATION REPORTS	eaton-dpq-5egen2-ups-certificate-en-gb.pdf
MANUALS AND USER GUIDES	eaton-dpq-5egen2-ups-manual-en-gb.pdf
TECHNICAL DATA SHEETS	eaton-dpq-5egen2-ups-datasheet-en-gb.pdf

RUNTIME GRAPH	View runtime graph
BATTERY MANAGEMENT	Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	No
COMMUNICATION	USB port (HID compliant)
EXPANSION SLOTS	No
ETHERNET INTERFACE	No
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
USER INTERFACE	LEDs
TYPE OF INTERFACE	USB
POTENTIAL FREE SWITCH CONTACT	No
RELATIVE HUMIDITY	0-90% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
OPERATING TEMPERATURE - MAX	40 °C
OPERATING TEMPERATURE - MIN	0 °C
OUTPUT APPARENT POWER	2200 VA
INPUT VOLTAGE - MAX	300 V
INPUT VOLTAGE - MIN	140 V
OUTPUT VOLTAGE - MAX	257 V
OUTPUT VOLTAGE - MIN	195 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz
BATTERY QUANTITY	2
EFFICIENCY AT MAX. LOAD	95
INPUT VOLTAGE RANGE	140-300 V
OUTPUT FREQUENCY	50/60 Hz
OUTPUT VOLTAGE RANGE	195-257 V
PHASE (INPUT)	1

PHASE (OUTPUT)	1
POWER CONSUMPTION	63.2 W

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

