

Specifications

Eaton 9SX5KIRT3UG2



Eaton 9SX Gen2 UPS, 5000 VA, 5000 W,
Input: Hardwired, Outputs: (8) C13, (3) C19,
Hardwired, Rack/tower, 3U, Rack-mounting
kit included



General specifications

PRODUCT NAME	Eaton 9SX Gen2 UPS
CATALOG NUMBER	9SX5KIRT3UG2
EAN	3553340710650
PRODUCT LENGTH/DEPTH	684 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	440 mm
PRODUCT WEIGHT	43.1 kg
WARRANTY	2 year
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM KCC BSMI
MODEL CODE	Eaton 9SX 5000i RT3U G2

Additional information

CONSTRUCTION TYPE	482.6 mm (19 inch) device
PACKAGE CONTENTS	• UPS • (2) cable glands • (2) IEC-IEC output cables (1,2m) • USB cable (1,8m) • Cable locking systems • Supports for tower mounting • Rack-mounting kit with brackets and slides for UPS • Safety instructions • Quickstart guide
INTERNAL BYPASS	Yes
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
EFFICIENCY AT MAX. LOAD	96.7
RACK MOUNTING KIT	Yes
HOT SWAP POWER	No

Battery

BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	View runtime graph
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY QUANTITY	15
BATTERY MANAGEMENT	• ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable) • Automatic battery test • Deep discharge protection • Automatic recognition of external battery units
BATTERY RATING	12 V / 5 Ah
EXTENDED BATTERY CAPABILITY	Yes

Communication

INCLUDES NETWORK CARD	No
-----------------------	----

COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini terminal block for remote On/Off
- Mini-terminal block for remote power off
- Mini-terminal block for dry contacts outputs (2 contacts)

ETHERNET INTERFACE	No
--------------------	----

USER INTERFACE	Multilingual graphical LCD display
----------------	------------------------------------

POTENTIAL FREE SWITCH CONTACT	Yes
-------------------------------	-----

EXPANSION SLOTS	One slot
-----------------	----------

SOFTWARE COMPATIBILITY	Eaton Brighthouse Software suite
------------------------	----------------------------------

TYPE OF INTERFACE	Other
-------------------	-------

Electrical input

NOMINAL FREQUENCY	50/60 Hz
-------------------	----------

INPUT POWER FACTOR	>.99
--------------------	------

INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
---------------------	-------------------------------------

INPUT FREQUENCY RANGE	40-70 Hz
-----------------------	----------

Electrical output

RECEPTACLE	(8) C13, (3) C19, Hardwired
------------	-----------------------------

VOLTAGE	230V
---------	------

VA RATING	5000 VA
-----------	---------

WATTAGE	5000W
---------	-------

OUTPUT POWER FACTOR	1
---------------------	---

OUTPUT WAVEFORM	Sine wave
-----------------	-----------

OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
------------------------	--

VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	1
---	---

FEED TYPE	1
-----------	---

TOPOLOGY	Online/Double-conversion
----------	--------------------------

Environmental

ALTITUDE	3000 m
----------	--------

NOISE LEVEL	<40 dB at 1 meter
-------------	-------------------

TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
-------------------	---------------------------

RELATIVE HUMIDITY	0-95% non-condensing
-------------------	----------------------

Resources

BROCHURES	Eaton 9SX Gen2 UPS Datasheet - EN
COMPLIANCE INFORMATION	Eaton single phase UPS Transportation document according to DGR
DECLARATIONS OF CONFORMITY	Eaton 9SX Gen2 Declaration of Conformity
MANUALS AND USER GUIDES	Eaton 9SX Gen2 UPS Advanced User Guide - EN
PEP ECO-PASSPORT	eaton-double-conversion-network-ups-pep-eaton-00281-v0102-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

