

Specifications

Photo is representative

Eaton 9PX11KIRTNBPG2

Eaton 9PX Gen2 UPS HotSwap Netpack,
11000 VA, 11000 W, Input: Hardwired,
Outputs: (4) C39, Hardwired, Rack/tower, 4U,
Gigabit Network card included, Rack-
mounting kit included, Maintenance bypass
included

General specifications

PRODUCT NAME	Eaton 9PX Gen2 UPS
CATALOG NUMBER	9PX11KIRTNBPG2
MODEL CODE	Eaton 9PX 11000i RT4U HotSwap Netpack G2
EAN	3553340710629
PRODUCT LENGTH/DEPTH	725 mm
PRODUCT HEIGHT	174 mm
PRODUCT WIDTH	440 mm
PRODUCT WEIGHT	83.4 kg
WARRANTY	3 year on electronics, 2 year on battery
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM



Powering Business Worldwide

Additional information

AUTO SHUTDOWN FUNCTION	Yes
-------------------------------	-----

COLOR	Black/silver
--------------	--------------

CONSTRUCTION TYPE	482.6 mm (19 inch) device
--------------------------	---------------------------

EFFICIENCY AT MAX. LOAD	97
--------------------------------	----

HOT SWAP POWER	Yes
-----------------------	-----

INTERNAL BYPASS	Yes
------------------------	-----

PACKAGE CONTENTS

- UPS
- (3) cable glands
- (2) IEC-IEC output cables (1,2m)
- USB cable (1,8m)
- Network Management Card
- Maintenance Bypass
- Supports for tower mounting
- Rack-mounting kit with brackets and slides for UPS
- Mounting kit for Maintenance Bypass
- Safety instructions
- Quickstart guide

RACK MOUNTING KIT	Yes
--------------------------	-----

Battery specifications

BATTERY MANAGEMENT

- ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable)
- Automatic battery test
- Deep discharge protection
- Automatic recognition of external battery units

BATTERY QUANTITY	20
-------------------------	----

BATTERY RATING	12 V / 9 Ah
-----------------------	-------------

BATTERY TYPE	Sealed, lead-acid
---------------------	-------------------

EXTENDED BATTERY CAPABILITY	Yes
------------------------------------	-----

RUNTIME GRAPH	View runtime graph
----------------------	------------------------------------

Communication

COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini terminal block for remote On/Off
- Mini-terminal block for remote power off
- Mini-terminal block for dry contacts outputs (2 contacts)
- Network card

ETHERNET INTERFACE	Yes
--------------------	-----

EXPANSION SLOTS	2 slots, network card included
-----------------	--------------------------------

INCLUDES NETWORK CARD	Yes
-----------------------	-----

POTENTIAL FREE SWITCH CONTACT	Yes
-------------------------------	-----

SOFTWARE COMPATIBILITY	Eaton Brighthouse Software suite
------------------------	----------------------------------

TYPE OF INTERFACE	Other
-------------------	-------

USER INTERFACE	Multilingual graphical LCD display
----------------	------------------------------------

Electrical output

FEED TYPE	1
-----------	---

OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
------------------------	-------------------------------------

OUTPUT POWER FACTOR	1
---------------------	---

OUTPUT VOLTAGE RANGE	200/208/220/230/240 V +/- 1%
----------------------	------------------------------

OUTPUT WAVEFORM	Sine wave
-----------------	-----------

RECEPTACLE	(8) C13, (8) C39, Hardwired
------------	-----------------------------

TOPOLOGY	Online/Double-conversion
----------	--------------------------

VA RATING	11 kVA
-----------	--------

VOLTAGE	230V
---------	------

VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	1
---	---

WATTAGE	11 kW
---------	-------

Electrical input

INPUT FREQUENCY RANGE	40-70 Hz
-----------------------	----------

INPUT POWER FACTOR	>.99
--------------------	------

INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
---------------------	-------------------------------------

NOMINAL FREQUENCY	50/60 Hz
-------------------	----------

Environmental

ALTITUDE	3000 m
----------	--------

NOISE LEVEL	<37 dB at 1 meter
-------------	-------------------

RELATIVE HUMIDITY	0-95% non-condensing
-------------------	----------------------

TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
-------------------	---------------------------

Resources

BROCHURES	Eaton 9PX Gen2 EMEA Brochure - EN
COMPLIANCE INFORMATION	Eaton single phase UPS Transportation document according to DGR
DECLARATIONS OF CONFORMITY	Eaton 9PX Gen2 Declaration of Conformity
MANUALS AND USER GUIDES	Eaton 9PX Gen2 UPS Advanced user guide - EN
MULTIMEDIA	Eaton 9PX Gen2 Video

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

