



## WV-SW155/WV-SW152 DOME NETWORK CAMERAS FOR USE WITH THE i-PRO TRANSIT SYSTEM

- 720 HD images up to 30 fps (WV-SW155)
- Multiple H.264 and JPEG streams for real-time monitoring and recording
- Wide coverage (Horizontal: 104°, Vertical: 85°)
- Super Dynamic and Adaptive Black Stretch technologies deliver 128x wider dynamic range compared to conventional cameras
- SDHC/SD memory card slot for manual recording (H.264/JPEG), alarm recording (H.264/JPEG) and backup recording upon network failure (JPEG)
- IP66-rated for water and dust resistance



(WV-SW155)



## RELIABLE IMAGING QUALITY AND VANDAL-RESISTANT DESIGN FOR INDOOR/OUTDOOR ENVIRONMENTS.

The vandal-resistant Panasonic i-PRO SmartHD WV-SW155 and WV-SW152 dome network cameras are low profile with an IP66 design for the ability to survive the harshest environments. With Super Dynamic and Adaptive Black Stretch technologies, they deliver a 128x wider dynamic range than conventional cameras for increased visibility of subjects in dark areas with no degradation of the image quality in brighter areas. Featuring high-resolution processing by UniPhier®, they deliver full-frame rate transmission at up to 30 fps for reliable surveillance capability.

# Super Dynamic HD Vandal-resistant Dome Network Camera

## WV-SW155/WV-SW155M

# Super Dynamic Vandal-resistant Dome Network Camera

## WV-SW152/WV-SW152M

# Panasonic

CAMERA	
Image Sensor	1/3 type MOS image sensor
Effective Pixels	Approx. 1.3 megapixels
Scanning Mode	Progressive
Scanning Area	4.8 mm (H) x 3.6 mm (V) [3/16" (H) x 5/32" (V)]
Minimum Illumination	WV-SW155: Color: 0.8 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.05 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High)) BW: 0.6 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.04 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High)) WV-SW152: Color: 0.6 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.04 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High)) BW: 0.4 lx (F2.2, Auto slow shutter: Off (1/30s), Gain: On (High)) 0.03 lx (F2.2, Auto slow shutter: Max. 16/30s, Gain: On (High))
White Balance	AWC (2,000-10,000 K), ATW1 (2,700-6,000 K), ATW2 (2,000-6,000 K)
Light Control Mode	Indoor scene (50 Hz / 60 Hz) / ELC
ELC (Maximum Exposure Time)	With Super Dynamic ON ELC (1/30s) With Super Dynamic OFF ELC (1/30s), ELC (3/100s), ELC (3/120s), ELC (2/100s), ELC (2/120s), ELC (1/100s), ELC (1/120s), ELC (1/250s), ELC (1/500s), ELC (1/1,000s), ELC (1/2,000s), ELC (1/4,000s), ELC (1/10,000s)
Day & Night (Electrical)	OFF / AUTO
Digital Noise Reduction	HIGH/LOW
Face Detection	ON/OFF (with the XML notification setting)
Super Dynamic	ON/OFF
Dynamic Range	52 dB typ. (Super Dynamic: ON, Light Control: ELC)
Adaptive Black Stretch	ON/OFF
AGC	ON (HIGH) / ON (MID) / ON (LOW) / OFF
Auto Slow Shutter	OFF (1/30 s), Max. 2/30 s, Max. 4/30 s, Max. 6/30 s, Max. 10/30 s, Max. 16/30 s
Video Motion Detection	ON / OFF, 4 areas available
Privacy Zone	ON / OFF (up to 2 zones available)
VIQS	ON/OFF
Camera Title	Up to 20 characters (alphanumeric characters, marks), On/Off
LENS	
Focal Length	1.95 mm
Zoom Ratio	1x / Extra zoom: 2x (under VGA resolution)
Maximum Aperture Ratio	01:02.2
Adjusting Angle	Ceiling Installation H: -20° to +20°, V: -20° to +90° Wall Installation H: -80° to +80°, V: -90° to +20°
Angular Field of View	Horizontal: 104°, Vertical: 85°
BROWSER GUI	
Supported OS <sup>2,3</sup>	Microsoft® Windows® 7, Microsoft® Windows Vista®, GUI Microsoft® Windows® XP SP3
Supported Browser	Windows® Internet Explorer® 9.0 (32 bit) Windows® Internet Explorer® 8.0 (32 bit) Windows® Internet Explorer® 7.0 (32 bit) Microsoft® Internet Explorer® 6.0 SP3
NETWORK	
Network IF	WV-SW155/WV-SW152 10Base-T / 100Base-TX, RJ-45 connector (female) WV-SW155M/WV-SW152M 10Base-T / 100Base-TX, M-12 connector (male)
Image Resolution	Aspect ratio: [4:3] WV-SW155: H.264: 1,280 x 960 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps JPEG (MJPEG): 1,280 x 960 / 640 x 480 / 320 x 240, up to 30 fps WV-SW152: H.264: 800 x 600 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps JPEG (MJPEG): 800 x 600 / VGA (640 x 480) / QVGA (320 x 240), up to 30 fps Aspect ratio: [16:9] WV-SW155: H.264: 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps JPEG (MJPEG): 1,280 x 720 / 640 x 360 / 320 x 180, up to 30 fps WV-SW152: H.264: 640 x 360 / 320 x 180, up to 30 fps JPEG (MJPEG): 640 x 360 / 320 x 180, up to 30 fps Frame Rate 1 / 3 / 5 / 7.5 / 10 / 15 / 20 / 1 / 3 / 5 / 7.5 / 10 / 12 / 15 / 20 / 30 fps Bit Rate/Client Constant Bit Rate / Best effort: 64 kbps / 128 kbps / 256 kbps / 384 kbps / 512 kbps / 768 kbps / 1,024 kbps / 1,536 kbps / 2,048 kbps / 3,072 kbps / 4,096 kbps / 8,192 kbps (WV-SW155) Image Quality LOW / NORMAL / FINE Transmission Type UNICAST / MULTICAST

NETWORK (CONT.)		
JPEG (MJPEG) <sup>4</sup>	Image Quality	0 SUPER FINE / 1 FINE / 2 / 3 / 4 / 5 NORMAL / 6 / 7 / 8 / 9 LOW (10 steps: 0-9)
	Transmission Type	PULL / PUSH
Transmission Interval	0.1 fps - 30 fps (JPEG frame rate will be restricted when displaying both JPEG and H.264 images.)	
Bandwidth Control	64 / 128 / 256 / 384 / 512 / 768 / 1,024 / 2,048 / 4,096 / 8,192 kbps / Unlimited	
Supported Protocol	IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, RTP, FTP, SMTP, DNS, NTP, SNMP, DHCPv6 IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP	
FTP Client	Alarm image transmission, FTP periodic transmission (When the FTP transmission is failed, backup on an optional SDHC/SD memory card is available.)	
Multi-Screen	Up to 16 camera images can be displayed simultaneously on a multi-screen. (Including the camera itself)	
Maximum Concurrent Access Number	14 (Depends on network conditions)	
SDHC/SD Memory Card (Option)	Manufactured by Panasonic SDHC memory card: 4 GB, 8 GB, 16 GB, 32 GB SD memory card: 256 MB, 512 MB, 1 GB, 2 GB (except miniSD card and microSD card)	
Cellular Phone Compatibility	JPEG Image	
Mobile Terminal Compatibility	iPAD, iPhone, iPod touch	
ALARM		
Alarm Source	VMD, Command alarm	
Alarm Actions	E-mail notification, Indication on browser, FTP image transfer, Panasonic protocol output	
Alarm Log	ON/OFF	
Schedule	VMD	
GENERAL		
Power Source/Consumption	PoE (IEEE802.3af compliant) / PoE 48 V, 56 mA (Class 1 device)	
Ambient Operating Temperature/Humidity	-30°C to +50°C (14°F to 122°F) / Less than 90% (no condensation)	
Waterproof	Camera: IP66 (IEC60529) <sup>5</sup>	
Shock Resistance	Compliant with 50 J IEC60068-2-75	
Dimensions	109 mm x 47 mm (H) [6-15/32" x 5-3/4" (H)]	
Mass (approx.)	350g (0.77 lbs.)	
Finish	Main body: Aluminum die cast, light gray Dome section: Clear polycarbonate resin	

<sup>1</sup> Converted value

<sup>2</sup> Refer to "Notes on Windows Vista® / Windows® 7" on the provided CD-ROM for further information about system requirements for a PC and precautions when using Microsoft® Windows® 7 or Microsoft® Windows Vista®

<sup>3</sup> When using IPv6 for communication, use Microsoft® Windows® 7 or Microsoft® Windows Vista®

<sup>4</sup> Transmission for 2 streams can be individually set in the same compression method

<sup>5</sup> Only when installation work specified in this book is properly performed and appropriate waterproof treatment is performed



1.855.333.4035

us.panasonic.com/security

Microsoft and Windows are registered trademarks of Microsoft Corporation in the U.S. and other countries. iPad, iPhone and iPod touch are registered trademarks of Apple Inc. ONVIF and the ONVIF logo are trademarks of ONVIF Inc. UniPhier is a registered trademark of Panasonic Corporation. "Super Dynamic", "SD1I", "SD1II", "SD5", "SD5Link", "i-PRO" and "i-PRO SmartHD" logos are trademarks or registered trademarks of Panasonic Corporation. Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. ©2014 Panasonic Corporation of North America. All rights reserved. WV-SW155/152 Spec\_Sheet\_07/14

**i-PRO**  
**SmartHD**