

# **Automotive Accessories**

#### TP81 and TP82 Insulation Piercing Clip Set

- Banana jack accepts all DMM and banana iack leads
- Non-rotating banana jack prevents leads from tangling, allowing you to tighten/loosen clamp while still connected to the test lead
- Available for 4 mm input, modular connection with TP81 or available as a 2 mm input to slip onto probe tips with the TP82
- Tested to 60 V DC



### TLK282 SureGrip™ Deluxe Automotive Test Lead Kit Kit contains:

- TP81 Insulation Piercing Clip Set
- TP40 Automotive Back Probe Pins (five)
- TL224 Suregrip™ Silicone Test Lead Set TP220 Suregrip™ Test Probe Set AC220 Suregrip™ Alligator Clip Set
- AC285 Suregrip™ Large Jaw Alligator
- AC280 Suregrip™ Hook Clip Set
- Soft Case



#### TP84 Oxygen Sensor Insulation Piercing Clip

- · Banana jack accepts all DMM and banana jack leads
- Non-rotating banana jack prevents leads from tangling, allowing you to tighten/loosen clamp while still connected to the test lead
- Tested to 60 V DC



#### TP88 Rigid Back Probe Pin Set

- Slides onto test probes measuring 2 mm
- Tested to 60 V DC



#### TP40 Automotive Back Probe Pins (five)

- · Banana jack accepts all DMM and banana jack leads
- Tested to 60 V DC



## BP880 BNC to Female Double Stacking Banana Plug BP881 BNC to Male Double Stacking Banana Plug

- · Allows for hands-free testing in controlled voltage environments 500 VRMS maximum
- · Banana plug is nickel-plated, beryllium copper for low contact resistance
- The BNC shell is plated for tarnish resistance
- Operating temperature +50°C maximum





RP881

#### PV350 Pressure Vacuum Module

- Compatible with all Fluke and most popular
- · Digital pressure and vacuum measurements in a single module
- Transducer sealed in 316 stainless steel compatible with variety of liquids and gases
- Measures vacuum to 76 cm Hg
- Display results in English (psig or Hg) or metric (kPa or cm Hg) units
- Measures pressure to 500 psig (3447 kPa)

#### TL28A Automotive Test Lead Set

- Flexible silicone insulated leads are heat and cold resistant
- Cat I 30 V, 10 A



# TLK281 SureGrip™ Automotive Test Lead Kit

#### Kit contains:

- TP81 Insulation Piercing Clip Set
- TL224 Suregrip<sup>™</sup> Silicone Test Lead
- TP220 Suregrip™ Test Probe Set
- AC220 Suregrip<sup>™</sup> Alligator Clip Set
   AC285 Suregrip<sup>™</sup> Large Jaw Alligator Clip Set
- Soft Case



#### 90i-610s AC/DC Current Probe (600 A)

- Current Range: 2 to 600A DC or AC Peak
- Basic Accuracy (DC to 400Hz): +/- (2% of reading + 1A)
- Output Signal: 100A range: 10mV/A 600A range: 1mV/A
- Frequency Range: 40Hz to 400Hz
- Working Voltage: 600V AC rms
- Maximum Conductor Diameter: 34 mm

# RPM80 Inductive Pick-up

• Provides RPM readings



Fluke. Keeping your world up and running.

### **Fluke Corporation**

P.O. Box 909 Everett, WA USA 98206

Fluke Europe B.V. P.O. Box 1186 5602 BD Eindhoven The Netherlands

For more information call: In the U.S.A. (800) 443-5853 or Fax (425) 446 -5116 In Europe/M-East/Africa +31 (0)40 2 675 200 or Fax +31 (0)40 2 675 222 In Canada (905) 890-7600 or Fax (905) 890-6866 From other countries +1 (425) 446 -5500 or Fax +1 (425) 446 -5116

### Visit us on the world wide web at: http://www.fluke.com

Fluke (UK) Ltd. 52 Hurricane Way Norwich Norfolk NR6 6JB United Kingdom Tel.: 0207 942 0700 Fax: 0207 942 0701 E-mail: industrial@uk.fluke.nl

© Copyright 2004 Fluke Corporation. All rights reserved. Printed in the Netherlands 08/04
Data subject to alteration without notice.
Pub\_ID: 10761-eng