

# Automotive Accessories

## TP81 and TP82 Insulation Piercing Clip Set

- Tested to 60 V DC
- Banana jack accepts all DMM and banana jack leads
- Non-rotating banana jack prevents leads from tangling, allowing you to tighten/loosen clamp while still connected to the test lead
- Available for 4 mm input, modular connection with TP81 or available as a 2 mm input to slip onto probe tips with the TP82



## TP84 Oxygen Sensor Insulation Piercing Probe

- Tested to 60 V DC
- Banana jack accepts all DMM and banana jack leads
- Non-rotating banana jack prevents leads from tangling, allowing you to tighten/loosen clamp while still connected to the test lead



## TP88 Rigid Back Probe Pin Set

- Tested to 60 V DC
- Slides onto test probes measuring 2 mm



## TP40 Automotive Back Probe Pins (five)

- Tested to 60 V DC
- Banana jack accepts all DMM and banana jack leads



## TL82 Automotive Pin & Socket Adapter Kit

- Tested to 60 V DC
- Kit contains:**
- Set of retractable shrouded test leads
- Complete set of 8 pin-and-socket adapters with flexible tips; one red and one black in the following sizes:  
Size 22 contact 0.76 mm rated 5 A  
Size 20 contact 1.02 mm rated 7.5 A  
Size 16 contact 1.60 mm rated 13 A  
Size 12 contact 2.36 mm rated 23 A



## BP880 BNC to Female Double Stacking Banana Plug BP881 BNC to Male Double Stacking Banana Plug

- Allows for hands-free testing in controlled voltage environments 500 VRMS maximum.
- Banana plug is nickel-plated, beryllium copper for low contact resistance
- The BNC shell is plated for tarnish resistance
- Operating temperature +50°C maximum



## PV350 Pressure Vacuum Module

- Measure pressure up to 500 psig (3447 kPa)
- Measure vacuum down to 76 cm in Hg



## TL28A Automotive Test Lead Set

- Flexible silicone insulated leads are heat and cold resistant
- Cat I 30 V, 10 A



## TLK282 SureGrip™ Deluxe Automotive Test Lead Kit

- Tested to 60 V DC
- Kit contains:**
- TP81 Insulation Piercing Clip Set
- TP40 Automotive Back Probe Pins (five)
- TL224 Suregrip™ Silicone Test Lead Set
- TP220 Suregrip™ Test Probe Set
- AC220 Suregrip™ Alligator Clip Set
- AC285 Suregrip™ Large Jaw Alligator Clip Set
- AC280 Suregrip™ Hook Clip Set
- Soft Case




## TLK281 SureGrip™ Automotive Test Lead Kit

- Tested to 60 V DC
- Kit contains:**
- TP81 Insulation Piercing Clip Set
- TL224 Suregrip™ Silicone Test Lead Set
- TP220 Suregrip™ Test Probe Set
- AC220 Suregrip™ Alligator Clip Set
- AC285 Suregrip™ Large Jaw Alligator Clip Set
- Soft Case



## 90i-610s AC/DC Current Probe (600 A)

- Current Range: 2 to 600A DC or AC Peak
- Basic Accuracy (DC to 400Hz): +/- (2% of reading + 1A)
- Output Signal: 100A range: 10mV/A | 600A range: 1mV/A
- Frequency Range: 40Hz to 400Hz
- Working Voltage: 600V AC rms
- Maximum Conductor Diameter : 34 mm



## RPM80 Inductive Pick-up

- Provides RPM readings



**Fluke.** *Keeping your world up and running.*

**Fluke Corporation**  
P.O. Box 9090  
Everett, WA USA 98206

**Fluke Europe B.V.**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands

For more information call:  
In the U.S.A. (800) 443-5853  
or Fax (425) 446-5116  
In Europe/M-East/Africa  
+31 (0)40 2 675 200  
or Fax +31 (0)40 2 675 222  
In Canada (905) 890-7600  
or Fax (905) 890-6866  
From other countries  
+1 (425) 446-5500  
or Fax +1 (425) 446-5116

Visit us on the world wide web at:  
**<http://www.fluke.com>**

Fluke (UK) Ltd.  
52 Hurricane Way  
Norwich  
Norfolk  
NR6 6JB  
United Kingdom  
Tel.: 0207 942 0700  
Fax: 0207 942 0701  
E-mail: [industrial@uk.fluke.nl](mailto:industrial@uk.fluke.nl)