

Slim and Flexible

Streamlined design equips with a foldable base; PS-3315 provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal top and the base, PS-3315 ensures neat, reliable peripheral cabling.

Specification	PS-3315
Processor	Intel Celeron N2807 processor, 1.58GHz/2.16GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	1 x SATA + 1 x eMMC connector
Power Supply	12V/30W
OS Support	Windows 7 / POSReady 7 / Windows Embedded 8.1 Industry / Linux per request
Display	
LCD Display	15" TFT LCD, 1024 x 768 resolution
Touch Function	5-wire resistive touch
Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	3 x DB9 + 1 x RJ45, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
UPS Port	N/A
Standard USB Port	5
PS/2 Port	1, via optional conversation cable
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
Audio	Buzzer only
WIFI	Optional internal mini-PCIe WIFI module with PIFA Antenna
Physical Dimension	
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.86
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Options	
SA-105	Side Attachment for PS Series with 3 track MSR
SA-205	Side Attachment for PS Series with iButton
SA-305	Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
SA-505	3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series
LM-6807U/LM-6810U	7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface)
PD-2609UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-360UE/PD-360R	2 x 20 LCD, rear-mount, USB with Virtual COM support (PD-360UE) / RS232(PD-360R)
PD-6807U	7" color LCD graphical line display, rear-mount (USB interface)
KP-500	40-key dynakey attachmentwith MSR or RFID option for 15"/17" XT series & 15"/15.6" PS series

* The product information and specifications are subject to change without prior notice.
* Please refer to the web site for more attachment options.

U.S Patent: 9004436

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

201504



POSIFLEX TECHNOLOGY INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller

A Robust, Economical Choice



PS-3315

Best Value Fanless POS Terminal

PS-3315 is a 15" touch screen fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represents one of the best value choices in the entry-level POS Terminal segment.