


DATASHEET



The world's first 12,000 lumens WUXGA 3LCD laser projector¹ offers superior images and a long-lasting, low maintenance performance

Promising long-life laser projection for large venues, the EB-L1500U is the world's first 12,000 lumens WUXGA LCD laser projector¹. Images will have rich, vivid colours thanks to Epson's 3LCD technology and equally high White and Colour Light Output. With flexible installation and low maintenance, this 4K enhanced projector offers a fit-and-forget solution for scenarios in which only superior projections will do.

Laser-sharp images

Ensure superb quality and the best possible delivery of presentations with this laser installation projector for large venues. Featuring 3LCD technology and equally high White and Colour Light Output, its WUXGA resolution images are vivid and bright, even in daylight. Including a newly developed inorganic phosphor wheel, the projector offers superior light and heat resistance to deliver excellent reliability. For a next-level viewing experience, the projector features 4K enhancement, giving images exceptional sharpness and clarity that lasts for up to 56,000 hours² thanks to a long laser life. A built-in camera is also included to ensure accurate image calibration.

Flexible positioning

Thanks to a new range of motorised lenses, including optional ultra-short throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image.



KEY FEATURES

- Laser light source technology Reliable and long-lasting picture quality (up to 56,000 hours²)
- Superior picture quality Enhanced light output; superior white balance; better colour matching
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for the real 4K effect
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with 5-year, 20,000 hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1.03 inch with C2 Fine	
IMAGE		
Colour Light Output	12,000 lumen- 8,400 lumen (economy) In accordance with IDMS15.4	
White Light Output	12,000 lumen - 8,400 lumen (economy) In accordance with ISO 21118:2012	
Resolution	WUXGA, 1920 x 1200, 16:10	
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	2,500,000 : 1	
Native Contrast	2,000 : 1	
Laser Light source	20,000 Hours Durability High, 30,000 Hours Durability Eco	
Portrait Colour Light Output	12,000 lm	
Portrait White Light Output	12,000 lm	
Keystone Correction	Manual vertical: \pm 45 °, Manual horizontal \pm 30 °	
Colour Reproduction	Upto 1.07 billion colours	
OPTICAL		
Projection Ratio	1.57 - 2.56:1	
Zoom	Motorized, Factor: 1 - 1.6	
Lens Shift	Motorized - Vertical \pm 60 %, horizontal \pm 18 %	
Lens position memory	10 positions	
Image Size	60 inches - 500 inches	
inage eize		
Projection Lens F Number	1.8-2.5	
Projection Lens F Number Focal Distance	1.8 - 2.5 36 mm - 57.35 mm	
Projection Lens F Number Focal Distance Focus	36 mm - 57.35 mm	
Focal Distance Focus	36 mm - 57.35 mm Motorized	
Focal Distance Focus Projection Distance Wide	36 mm - 57.35 mm	
Focal Distance Focus	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage Product dimensions	36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height)	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage Product dimensions Product weight	 36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23.8 kg 	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level	 36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23.8 kg Normal: 37 dB (A) - Economy: 30 dB (A) - Eco2: 1 dB (A) 	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Colour Included Software	 36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23.8 kg Normal: 37 dB (A) - Economy: 30 dB (A) - Eco2: 1 dB (A) White 	
Focal Distance Focus Projection Distance Wide Projection Distance Tele Projection Distance Wide/Tel CONNECTIVITY Interfaces Epson iProjection App ADVANCED FEATURES Features Video Colour Modes Projector control Security GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Colour	 36 mm - 57.35 mm Motorized 2 m - 17.2 m 3.3 m - 27.8 m e 1.99 m - 27.77 m Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI Ad-Hoc / Infrastructure 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Lens position memory Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection via: AMX, Crestron, Control4 Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 908 W, 597 W (economy), 0.5 W (standby), On mode power consumption as defined in JBMS 84 833 W AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 23.8 kg Normal: 37 dB (A) - Economy: 30 dB (A) - Eco2: 1 dB (A) White 	

EB-L1500U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- VGA cable
- Cable cover
- CD Manual



OPTIONAL ACCESSORIES

- Air Filter ELPAF51 EB-L1000 series V13H134A51
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- 3D Polarizer ELPPL01 V12H618A01
- Wireless LAN Adapter ELPAP10 V12H731P01
- HDBaseT Transmitter ELPHD01 V12H547041
- Quick Wireless Connect USB key ELPAP09 V12H005M09

OPTIONAL LENSES

- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM09 Mid throw 2 G7000/L1000 series V12H004M09

LOGISTICS INFORMATION

SKU	V11H792040
EAN code	8715946616841
Country of Origin	China

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie The EB-L1505U / EB-L1500U is the first and only 12,000Lm WUXGA LCD laser projector on the market as of February 2016.
 Laser life of up to 56,000h hours in custom mode



EB-L1500U

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.