

Key Features

Full HD 1080p, 3200 Lumens | Amazing color accuracy | Enhanced 10W speaker | Smart design




Product Description

The ViewSonic LightStream® PJD7720HD Full HD projector features 3,200 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design and a sleek black chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while SonicExpert™, ViewSonic's proprietary sound enhancement technology, powers a 10W speaker to deliver incredibly clear and audible sound. PortAll™ - a neatly designed and enclosed HDMI/MHL connection compartment, supports wireless HDMI dongles or MHL connectors, while a cable management hood eliminates unsightly cable clutter. With a smart design, the PJD7720HD is the ideal projector for

high definition presentations.






1920 x 1080 RESOLUTION



3,200 LUMENS



- 1. IR remote sensor
- 2. Projection lens
- 3. Elevation foot
- 4. PortAll (HDMI/MHL)
- 5. Audio In/Out
- 6. AC In
- 7. Focus / zoom rings
- 8. Control Panel
- 9. USB type Mini B
- 10. RS232
- 11. Kensington® Lock Slot
- 12. HDMI

1.49~1.64:1 THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Throw Distance:	3.25 – 35.73 ft. / 1.0 – 10.9 m
Throw Ratio:	1.49~1.64:1
Type:	0.65" 1080P DLP DC3
Lens:	1.1x Manual optical zoom / manual optical focus
Light Source (watt):	210
Light Source Life, Normal (hours):	4000
Light Source Life, Dynamic Eco-Mode (hours):	10000

Brightness (ANSI Lumens):3,200

Color Depth: 30 bits, 1.07B Color (10+10+10)

Resolution: 1920 x 1080

Dynamic Contrast Ratio: 22000:1

Aspect Ratio:16:9

Resolution Type: 1080p

Display Size (in.): 30 - 300 in. / 0.76 - 7.62 m

Video Signal:

Frequency Horizontal: 15–100KHz

Frequency Vertical: 24–120Hz

Compatibility:

PC Resolution (max): Up to 1920x1080 non-interlaced

Mac® Resolution (max): Up to 1920x1080 (may require MAC adapter)

Connector:

3.5mm Audio Out(1), 3.5mm Audio In(1), HDMI 1.4(1), HDMI MHL(1), Mini USB(1)

Audio:

Internal Speakers: 10W

Power:

Voltage: 100~240VAC (Auto Switching), 50-60Hz (universal)

Consumption (max): 330W

Stand-by: <0.5W

Controls:

Physical Controls: Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source

On Screen Display: Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature: 32-104° F (0–40° C)

Humidity (non-condensing): 10-90%

Additional Hardware:

Kensington Lock Slot: 1

Weight (imperial):

Net (lbs): 5.3

Gross (lbs): 8.4

Weight (metric):

Net (kg): 2.4

Gross (kg): 3.8

Dimensions (metric)

(WxHxD):

Packaging (mm): 410 x 225 x 450

Physical (mm): 316 x 228 x 103.7

Dimensions (imperial)

(WxHxD):

Packaging (in.): 16.14 x 8.86 x 17.72

Physical (in.): 12.44 x 8.98 x 4.08

General:

Regulations: Mexico Energy test/Registration, EAC, TUV-S Mark (Argentina), India BIS, FCC, CE EMC, CB, CCC, RoHS, REACH, SVHC, WEE, ErP, Mexico NOM, cTUVus, RCM, PSB, KC

PACKAGE CONTENTS: PJD7720HD projector, power cable, remote control (batteries included), Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: 1-year limited warranty on parts and labor, 90 day limited warranty on lamp

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907845617

Accessories:

PGD-350, PJ-CASE-009, PJ-CM-001, PJ-SCW-1001W, PJ-WMK-006, RLC-100, WPG-300

Copyright © ViewSonic Corporation 2000-2016. All rights reserved. (12/02/2016 11:33 PM PST)