

Panel

Diagonal Size	75	Type	120Hz LED BLU
Resolution	1920*1080 (Full HD)	Pixel Pitch(mm)	0.2865(H) × 0.8595(V)
Active Display Area(mm)	1650.24(H) × 928.26(V)	Brightness(Typ.)	400 nit
Contrast Ratio	5000:01:00	Viewing Angle(H/V)	178:178
Response Time(G-to-G)	4ms	Display Colors	10bit Dithering - 1.07Billion
Color Gamut	70%	Haze	N/A

Display

Dynamic C/R	Mega. DCR (AV Mode)	H-Scanning Frequency	30 ~ 81kHz
V-Scanning Frequency	48 ~ 75HZ	Maximum Pixel Frequency	148.5MHz

Display

Speaker Type	Built in Speaker(10W + 10W)
---------------------	-----------------------------

Connectivity

Input	RGB	Analog D-SUB, DVI-D
	Video	CVBS, Component, HDMI
	Audio	Stereo mini Jack
	Usb	USB Player
Output	RGB	N/A
	Video	N/A
	Audio	Stereo mini Jack
	Power Out	N/A
External Control	RS232C(in/out) thru stereo jack	
External Sensor	Yes	
Tuner	No	

Power

Type	Internal
Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption	Max[W/h]	275
	Typical[W/h]	215
	BTU(Max)	937.75
	Sleep mode	less than 0.5W
	Off mode	less than 0.5W

Mechanical Specification

Dimension (mm)	Set	1676.2x959.5x88.4(except handle 57.7)
	Package	1810X1085X250
Weight (kg)	Set	34.1
	Package	44.1
VESA Mount (mm)		400*400mm
Protection Glass		N/A
Stand Type		Foot Stand (Optional)
Media Player Option Type		N/A
Bezel Width (mm)		10.9mm(Bottom 16.9mm)

Operation

Recommended Usage Hours	16/7		
Operating Temperature	0.0 °C ~ 40.0 °C	Humidity	10.0 % ~ 80.0 %

Feature

Key Features		LED LFD
Special Features		Built in Speaker(10W + 10W), PIP/PBP, Narrow Bezel, Light Weight, RS232 In/Out 1 D-Sub & 1 HDMI, USB Player
Internal Player	Processor	N/A
	On-Chip Cache Memory	N/A
	Clock Speed	N/A
	Main Memory Interface	N/A
	Graphics	N/A
	Storage (FDM)	N/A
	Multimedia	N/A
	IO Ports	N/A

	Operating System	N/A
--	-------------------------	-----

Certification

Safety	<p>UL(USA) : cUL60950-1, CSA (Canada):cUL60950-1, TUV (Germany) : IEC60950-1/EN60950-1, NEMKO (Norway): IEC60950-1/EN60950-1, CB (Europe) : IEC60950-1/EN60950-1, KC (Korea) : K 60950-1, CCC (China) : GB4943.1-2011, PSB (Singapore) : PSB+IEC60950-1, EAC (Russia) : EAC+IEC60950-1, NOM (Mexico) : NOM-001-SCFI-1993, IRAM (Argentina) : IRAM+IEC60950-1, SASO (Saudi Arabia) :SASO+IEC60950-1, BIS(India) : IEC60950-1 / IS13252, INMETRO (Brazil):INMETRO+IEC60950-1, BSMI(Taiwan):BSMI+IEC60950-1, RCM</p>
EMC	<p>FCC (USA):Part 15, Subpart B Class A, CE (Europe) :EN55022:2006+A1:2007 EN55024:1998+A1:2001+A2:2003, VCCI (Japan): VCCI V-3 /2010.04 Class A, KCC/EK (Korea):KN13 / KN20, BSMI (Taiwan) : CNS13438 (ITE EMI) Class A / CNS13439 (AV EMI) / CNS14409 (AV EMS) / CNS14972 (Digital) , C-Tick (Australia) : AS/NZS CISPR22:2009 , CCC(China) :GB9254-2008 GB17625.1-2012 , GOST(Russia/CIS):GOST R 51317 Series,GOST 22505-97.EN55022:2006+A1:2007.EN55024:1998+A1:2001+A2:2003</p>
Environment	N/A

Accessory

Included		Quick Setup Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries
Optional	Stand	STN-L7585F
	Mount	WMN6575SD
	Specialty	CML450D (Ceiling Mount)

Media Player

Media Player	SBB (Optional)
---------------------	----------------