

> PRINT > COPY > SCAN > FAX

TASKalfa 6002i

MONOCHROME MULTIFUNCTIONAL FOR A3 FORMAT

IMPRESSIVELY FAST HEAVY-DUTY MFP.



With output and scan speeds of up to 60 ppm and 180 ipm respectively, the TASKalfa 6002i is a multifunctional device that keeps your productivity flowing. Heavy workloads are dealt with easily thanks to flexible, high-capacity finishing options and a paper capacity of up to 7,150 sheets, while its impressive range of digital document management functions is quickly accessible via an intuitive, large colour touch panel. Sensitive documents are protected too thanks to enhanced security functions.

- > Up to 60 pages per minute in A4 format
- > Standard print resolution of 1,200 x 1,200 dpi, 2 bit depth (equivalent of 4,800 x 1,200 dpi)
- > Flexible paper handling from A6 up to SRA3 and beyond for up to 7,150 sheets
- > Productive finishing options including booklet finishing
- > 4 GB RAM, 8 GB SSD + 320 GB HDD memory and storage
- > Highly productive colour scanning
- > Comprehensive support for all state-of-the-art mobile communications
- > Long-life components providing exceptional efficiency and reliability, and less waste



The TASKalfa 6002i is an impressively quick, multifunctional printer designed for the busiest of offices. Thanks to its extremely durable components, it guarantees efficiency and reliable operation at all times. The TASKalfa 6002i ensures minimum impact on the environment while providing effective productivity and maximum flexibility.

GENERAL

Technology: KYOCERA Laser Monochrome, HyPAS™

solution platform

Touch panel size: 22.8 cm (9 inch) full-colour touch panel

display, 15° – 90° swivel mounted Engine speed (pages per minute): Up to 60/30 ppm A4/A3 Resolution: 1,200 x 1,200 dpi, 2 bit depth for print quality

of 4,800 dpi equivalent x 1,200 dpi **Warm-up time from power on:** Approx. 17 seconds or less **Time to first page:** Approx. 3.4 sec. or less **CPU:** Freescale QorlQ T1024 (Dual Core) 1.2 GHz

Memory (standard max.): 4 GB RAM, 8 GB SSD - 320 GB HDD

Standard interface: 4x USB 2.0 (Hi-Speed), USB Host 2.0. Fast Ethernet 10 BaseT/100 BaseTX/1,000 BaseT, slot for optional print server, slot for optional SD card, slot for optional Fax System

Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm Weight: Main unit approx. 83 kg Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption: Printing: 820 W

Printing: 820 W
Ready mode: 40 W
Sleep mode: 1 W or less
Noise (sound pressure level ISO 7779/ISO 9296):
Printing: 54.8 dB(A) LpA
Ready mode: 34.6 dB(A) LpA
Safety standards: GS, TÜV, CE.
This unit is manufactured according to ISO 9001 quality
standard and ISO 1/4001 environmental standard. RoHs standard and ISO 14001 environmental standard. RoHs

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions. Input capacity:

150-sheet multipurpose tray, 52 – 300 g/m² (Banner 135 – 165 g/m²), A6R – SRA3 (320 x 450 mm), Tab paper (136 – 256 g/m²), Banner max. 320 x 1,220 mm; 2x 500-sheet universal paper cassette, 52 – 300 g/m², upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 **Duplex unit:** Duplex as standard supports A6R – SRA3 (320 x 450 mm), 64 – 256 g/m² Output capacity: Standard 500 sheets face-down, max.

PRINT FUNCTIONS

output capacity 4,300 sheets

Controller language: PRESCRIBE Emulations: PCL6 (PCL-XL/PCL-5e), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of onedimensional barcodes plus two-dimensional barcode

(PDI-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPV3, quick copy, proof and hold, Private Print, job storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Georgia Claud Print Google Cloud Print

COPY FUNCTIONS

Max. original size: A3 Continuous copying: 1–999 Zoom range: 25–400% in 1% steps

Preset magnification ratios: SR/SE
Digital features: Scan once copy many, electronic sort,
2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page

Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, map

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WSD scan Scan speed: (A4, 300 dpi, Dual Scan with DP-7110) b/w 180 images per minute, colour 180 images per minute Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit) **Max. scan size:** A3, Banner up to 1,900 mm with optional Document processor

Original recognition: Text, photo, text + photo, optimised for OCR

File types: PDF (high compressive, encrypted, PDF/A), Searchable PDF (option), JPEG, TIFF, XPS, Open XPS

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)
Fax resolution:
Normal: 200 x 100 dpi

Noninal: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 200 x 400 dpi Ultrafine: 400 x 400 dpi, 600 x 600 dpi Maximum original size: A3, Banner max. 1,600 mm Compression method: JBIG, MMR, MR, MH Features: Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

CONSUMABLES

TK-6325 Toner-Kit: Average continuous toner yield 35,000 pages in accordance with 6% coverage A4 WT-8500 Waste Toner Bottle: 40,000 pages (in accordance with 6% coverage) Staple cartridge: SH-10 for DF-7100, DF-7120, BF-730 SH-12 for DF-7110

Fax System (12) Internet Fax Kit (A)
Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR)

Paper handling DP-7100 Document processor: (Reversing), 140 sheets, DP-7100 Document processor: (Reversing), 140 sheets, 35 – 160 g/m² (simplex), A6R – Banner up to 1,900 mm DP-7110 Document processor: (one-path duplex scanning) 270 sheets, 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex), A6R – Banner up to 1,900 mm PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m², A6R – SRA3 (320 x 450 mm), folio PF-7110 Paper feeder: 2x 1,500 sheets, 52 – 300 g/m², A4, B5. letter

PF-7120 A4 side Deck: 3,000 sheets, 60 – 300 g/m², A4, B5 DT-730(B) Document tray DF-7110* Document finisher + AK-7100:

DF-7110' Document finisher + AK-7100:
Main tray: Max. 4,000 sheets A4 (3,000 sheets with attachment BF-730); max. 52 – 300 g/m²; max. A6R – SRA3
Sub tray: 200 sheets A4; 52 – 300 g/m²; A6R – SRA3
AK -7100: 100 sheets; 52 – 300 g/m²; A6R – SRA3
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5 – SRA3

B5 – SRA3
DF-7120' Document finisher + AK-7100:
Maintray: 1,000 sheets A4, 52 – 300 g/m², A6R – SRA3,
3 positions stapling up to 50 sheets A4 or 30 sheets SRA3
AK - 7100: 100 sheets; 52 – 300 g/m², A6R – SRA3,
'Bridge unit AK-7100 is required for the use of DF-7110 and

DF-7100 Inner finisher Max. 500 sheets; Max. 52 – 300 g/m², A6R – SRA3; Stapling up to 50 sheets at 3 positions A4 - A3 PH-7C/PH-7D Punch unit for DF-7120/DF-7110: 2-hole/4-hole/Swedish type, $60-300~g/m^2$, A5R-A3 MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, $60-165~g/m^2$ BF-730 Booklet and tri-folding unit for DF-7110 BF-/30 Booklet and tri-folding unit for DF-/TiU Half-folding: 52 – 256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60 – 90 g/m²) Non-staple folding: Max. 5 sheets (60 – 90 g/m²) Tri-folding: 60 – 105 g/m², A4R Multi tri-folding: 5 sheets (60 – 90 g/m²), 3 sheets $(91-105 \text{ g/m}^2)$

JS-7100 Job separator: 100-sheet internal job separator, 52 – 300 g/m², A5R – SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/

Swedish type Keybordholder 10

Security

Data security kit (E): In line with ISO 15408 (common criteria) with security level EAL3 NK-7100 Numeric keypad USB IC Card Reader: Card Authentication Kit (B)AC

UG-33: ThinPrint support
UG-34: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface IB-35: Direct Wi-Fi Interface

B-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1,000 BaseT IB-51: Wireless LAN Interface

Platen cover (E)

CB-7100W: Wooden cabinet CB-7110M: Metal cabinet

















www.kyoceradocumentsolutions.eu - info@deu.kyocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku - Osaka 540-8585 - Japan - www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.