

ViewSonic® LED DISPLAY **VA1903a**

Key Features

16:9 Widescreen Optimized for HD Content | ViewMode: Superior Color Rendering & Intuitive Settings | ViewSonic Flicker-Free viewing for improved eye comfort | Blue light filter for more comfortable viewing | Eco-mode Conserves More Energy and Cuts Costs



Product Description

The ViewSonic VA1903a is a 19"(18.5" viewable) LED monitor which is the ideal choice for corporate, educational or home office use. In addition to a 16:9 widescreen and energy saving Eco mode, it is also equipped with ViewSonic's exclusive ViewMode, providing intuitive presets that deliver optimized screen performance in different applications. Besides, Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods for improved productivity. Lastly a VESA-compatible mount adapt easily to multi-monitor or wall-mount set ups.

Visit Us

www.viewsonic.com

LCD

| | |
|---------------------|------------------------------------|
| Size: | 19" (16:9) |
| Panel Tecgnology: | TN |
| Display Area: | 18.5 inch |
| Optimum Resolution: | 1366x768 |
| Brightness: | 200 cd/m2 (Typ.) |
| Contrast Ratio: | 600 :1 (Typ.) |
| Viewing Angle: | 90° (H) / 65° (V) |
| Response Time: | Tr+Tf: 5ms (Typ.) |
| Panel Surface: | Anti-Glare type, Hard-coating (3H) |
| Light Source: | 30000 Hrs (Min.) |
| Color Support: | 16.7 M(6 bits +2 bits scalar FRC) |

INPUT

| | |
|----------------------|------------------------|
| Analog: | VGA |
| Frequency (Fh / Fv): | 24 ~82 kHz / 50 ~75 Hz |

COMPATIBILITY

| | |
|------|----------|
| PC: | 1366x768 |
| Mac: | 1366x768 |

CONNECTOR

| | |
|---------|----------------------|
| Analog: | VGA x1 |
| Power: | Internal Power Board |

POWER

| | |
|----------------|--------------------------------------|
| Voltage: | AC 100-240V (Universal); 50/60 Hz |
| Save mode (W): | ≤5W |

ERGONOMICS

| | |
|-------|-----------|
| Tilt: | 20° ~ -5° |
|-------|-----------|

OPERATING CONDITIONS

| | |
|--------------|---------------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity: | 10% to 90% (no condensation) |

VESA® WALL MOUNT (MM)

| |
|-------|
| 75x75 |
|-------|

PACKAGE CONTENTS

| |
|---|
| LCD Display/Power Cable/D-Sub Cable/Quick Start Guide |
|---|