



LED DISPLAY

VX2370S-LED

Key Features

Widescreen Full HD 1080p with SuperClear® technology | Frameless Flush Surface | 178/178 Degree Super Wide Viewing Angles | sRGB Color Correction Defines the Truest Color | Superlative 30,000,000:1 MEGA Dynamic Contrast Ratio



Product Description

The ViewSonic® VX2370S-LED features an LED backlit 23" frameless design widescreen monitor with up to 40%* energy savings compared to a regular 23" monitor. The environmentally-friendly mercury-free VX2370Smh-LED/VX2370S-LED offers Full HD 1920x1080 resolution, DVI with HDCP and VGA inputs, external power supply, and 30,000,000:1 MEGA Dynamic Contrast Ratio. A stylish glossy ID and thin profile combine to make it the center piece of your home or office. The SuperClear® technology with wide viewing angles and high contrast ratio deliver extraordinary visual clarity, making VX2370S-LED an excellent choice for entertainment and gaming. The industry's best pixel performance policy, energy saving Eco-mode, and Windows® 7 certification help ensure the product quality of VX2370S-LED.

Visit Uswww.viewsonic.com

LCD

Type:	23" Wide Color TFT Active Matrix IPS LED
Display Area:	23 inch
Optimum Resolution:	1920x1080
Contrast Ratio:	1,000:1 (typical), 30,000,000:1 (DCR)
Brightness:	250 cd/m ² (typ)
Viewing Angles:	178° horizontal, 178° vertical
Response Time:	4ms (GTG fastest), 7ms (GTG typical)
Panel Surface:	Anti-glare, hard-coating (3H)
Light Source:	30,000 Hrs (Min.)

VIDEO INPUT

Analog:	RGB analog (0.7 / 1.0 Vp-p, 75 ohms)
Digital:	DVI-D
Frequency:	Fh: 24-83KHz; Fv: 50- 76Hz
Sync:	Separate Sync

COMPATIBILITY

PC:	PC compatibles(from VGA up to 1920x1080 non-interlaced)
Mac:	Up to 1920x1080

CONNECTOR

Analog:	15-pin mini D-sub (VGA)
Digital:	DVI-D
Power:	External Power Adapter

AUDIO

Speakers:	1.5-watt (x2)
-----------	---------------

POWER

Voltage:	AC 100–240V (universal), 50 / 60Hz
Consumption:	(ECO Mode) Standard: 27W (typ); Optimize: 23W (typ); Conserve: 20W (typ)

OPERATING CONDITIONS

Temperature:	32–104°F (0–40°C)
Humidity:	20%-90% (non- condensing)

DIMENSIONS

Physical:	532.6mm (width) x 409mm (height) x 179.5mm (depth)
-----------	--

WEIGHT

Net:	3.9 kg
------	--------

REGULATIONS

CE, CB, BSMI, SASO, C-tick, e-standby, KC, UL/cUL, FCC-B (including ICES003), NOM, GOST-R/Hygienic, UkrSEPRO, Erp, CCC, China Energy, EPEAT Silver, WEEE, RoHS, SVHC list

PACKAGE CONTENTS

VX2370S-LED display, power cable, AC/DC adapter, VGA cable, HDMI cable, Quick Start Guide