

# ViewSonic® LED DISPLAY **VX2573-sg**

## Key Features

Stylish Borderless Bezel and Glossy-Finish Design | Low EMI promises a safer, unimpaired viewing experience | SuperClear® AH-IPS Enhancement Technology with wide viewing angles | ViewSonic Flicker-Free viewing for improved eye comfort | Blue light filter for more comfortable viewing



## Product Description

The ViewSonic VX2573-sg is a stylish 25" Full HD LED monitor with a borderless, glossy-finish and gold and black colour design, which is ideal for homes with contemporary décors. In addition to 1920 x 1080 resolution and 80M:1 dynamic contrast ratio, it is equipped with SuperClear® AH-IPS technology, delivering a 178 /178 degree wide viewing angle and stunning image quality with brilliant visual performance. It also comes with Flicker-free and Blue Light Filter eye-care technologies, ViewMode technology for optimal color rendering for different scenarios. With an amazingly convenient My Button hotkey design, it allows users to easily access these functions for further adjustment with one press of the finger. This monitor also features low EMI emissions for a reliable and sincere commitment to our end users' health. A wall mount design offers additional mount flexibility to set up this stylish, high-performance monitor at your home.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**LCD**

Type:	25" Wide Color IPS LCD (AH-IPS Panel)
Display Area:	25 inch
Optimum Resolution:	1920x1080
Contrast Ratio:	1,000:1 (typical), 80,000,000:1 (DCR)
Brightness:	250 cd/m <sup>2</sup> (typ)
Viewing Angles:	178°/178°
Response Time:	5ms (GTG $\sigma$ )
Panel Surface:	Anti-Glare type, Hardness 3H
Light Source:	30,000 Hours
Colors:	16.7 M

**PACKAGE CONTENTS**

LCD Display, AC, DC Adapter, Power Cable, VGA Cable, Quick Start Guide, View Sonic Wizard CD-ROM

**VIDEO INPUT**

Frequency:	Fh: 24-82KHz; Fv: 50-75Hz
Sync:	Separate Sync/Composite Sync/Sync on Green

**COMPATIBILITY**

PC:	1920x1080 (Non Interlaced)
Mac:	1920x1080

**ERGONOMICS**

Tilt:	15°~ -5°
-------	----------

**CONNECTOR**

Analog:	VGAx1
Digital:	DVIx1
Power:	External Adapterx1

**POWER**

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	24W ; 20W (Optimize) ; 17W (Conserve)

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F / 0°C to 40°C
Humidity:	10% to 90% (no condensation)

**DIMENSIONS**

Physical:	577mm (width) x 438mm (height) x 190mm (depth)
-----------	---

**WEIGHT**

Net:	4.0 kg
------	--------

**REGULATIONS**

BSMI, CB, CCC, VCCI, MEPS, CE, WEEE, RoHS2, REACH, EPEAT Silver

**WALL MOUNT**

VESA®100 x 100 mm