

ViewSonic® LED DISPLAY VX2880ml

Key Features

Stunning 4K Ultra HD Resolution on the Desktop | 10-bit colour processing for an amazing 1.07 billion colours | High-Definition Daisy Chain Capability | MHL functionality for easy connection to mobile devices | Dual Integrated Stereo Speakers



Product Description

The ViewSonic VX2880ml is a 28" 3840 x 2160 Ultra HD display that provides the highest resolution available in a desktop monitor. Delivering four times the pixels of Full HD displays, the VX2880ml features 4K resolution, 1.07 billion colours, and a 50M:1 Mega Dynamic Contrast Ratio for the ultimate in image colour, clarity, and detail. Versatile connectivity options include HDMI (MHL) for connection to smartphones and tablets, as well as dual DisplayPort inputs and one DisplayPort output for daisy-chain functionality. Dual integrated speakers provide enhanced audio for great multimedia and entertainment performance, while a VESA-mountable design offers additional convenience for use as a wall-mounted display. ViewSonic's proprietary Flicker-Free technology and blue light filter helps to eliminate eye strain from extended viewing periods. The ViewSonic VX2880ml is the perfect 4K multimedia display for power and professional users, including CAD/CAM drawing, content design, and development applications.

Visit Us www.viewsonic.com

LCD

Optimum Resolution:	3840 x 2160 (30Hz)
Contrast Ratio:	1000 :1 (Typ.)
Viewing Angles:	170° / 160° (Typ.)
Response Time:	5ms (Typ)
Display Area:	620.9 (H) x 341.3 (V) mm
Colour Support:	1.07 Billion
Size:	28" Colour Active Matrix TFT LCD
Brightness:	300 cd/m2 (Typ.)
Dynamic Contrast Ratio:	50M:1
Backlight:	WLED
Backlight Life:	30,000 Hrs (Min)

COMPATIBILITY

PC:	PC Compatibles (from 3840 x 2160 DP /HDMI Non Interlaced)
Mac@:	Power Mac (from 3840 x 2160 HDMI/DP)

CONNECTOR

Power:	External Adapter
Audio Out:	3.5mm plug x1
Video Input:	DisplayPort x1, Mini DisplayPort x1, HDMI(MHL) x1
Video Output:	DisplayPort x 1 (Daisy Chain capable)
Speaker:	2W x2

DIMENSIONS

Physical With Stand:	659.96 x 510.58 x 240 mm
Physical Without Stand:	659.96 x 412.46 x 52 mm
Packaging:	732 x 462 x 162 mm

REGULATIONS

CE, ErP, REACH, CU, Ukraine, Windows8

PACKAGE CONTENTS

<ol style="list-style-type: none"> LCD Display Adaptor Power Cable DP Cable MHL Cable Quick Start Guide mini DP cable
*Actual content may differ from market to market

INPUT SIGNAL

Video:	Display Port/ Mini Display Port/ MHL2.0(HDMI 1.4)
--------	---

POWER

Conserve:	28 W
Voltage:	AC 100~240V 50/60Hz
Consumption:	44 W
Optimize:	35 W

VESA® MOUNT

100 x 100 mm

ERGONOMICS

Tilt:	-5 ~ 20 degrees
-------	-----------------

WEIGHT

Gross:	7 kg
Net With Stand:	4.6 kg
Net Without Stand:	4.4 kg

OPERATING CONDITIONS

Temperature:	0°C to 40°C
Humidity:	20% to 90% (no condensation)