

Guide Number 18 m/59 ft. (at ISO 100)	Bounce Function (Tilt) Flash head tilts up to 120° with click stops at 0°, 60°, 90°, 120°	Weight (Approx. without batteries) 3.4 oz. (97 g)
Lens Coverage 18/27 to 200mm (DX/FX-format, Automatic mode)	Dimensions 2.3 x 2.6 x 2.5 in. (57.4 x 65.4 x 62.3 mm) (Approx.)	

Guide Number	18 m/59 ft. (at ISO 100)
Electronic Construction	Automatic Insulated Gate Bipolar Transistor (IGBT) and series circuitry
Flash Exposure Control	i-TTL Balanced Fill-Flash with CLS compatible cameras
Lens Coverage	18/27 to 200mm (DX/FX-format, Automatic mode)
Other Available Functions	Test Firing Monitor Pre-flashes Bounce capability
Bounce Function (Tilt)	Flash head tilts up to 120° with click stops at 0°, 60°, 90°, 120°
Minimum Recycling Time	3.5 sec. (approx.) with Ni-MH batteries 4.0 sec. (approx.) with Alkaline-manganese (1.5V) batteries
Required Power Source	Two AAA-size batteries
Ready Light	Back
Minimum Number of Flashes / Recycling Time	70 or more (1.5V Alkaline-manganese) 110 or more (Ni-MH batteries)
Dimensions	2.3 x 2.6 x 2.5 in. (57.4 x 65.4 x 62.3 mm) (Approx.)
Weight (Approx. without batteries)	3.4 oz. (97 g)