

Tech Specs & Customization

Display

Diagonal Viewable Size:
18.5" (46.99cm)
Aspect Ratio
Widescreen (16:9)
Panel Type:
TN - Twisted Nematic
Optimal Resolution:
1366 X 768 at 60Hz
Contrast Ratio:
1000 to 1 (typical)
Brightness:
250 CD/m2 (typical)
Response Time:
5ms panel typical
Viewing Angle
(160° vertical / 170° horizontal)
Color Support:
16.7 million colors
Pixel Pitch:
0.300mm
Device Type
Flat Panel Display

Stand

Tilt feature
On screen display controls (configurable) and
built-in cable management

VESA Mounting Support

Yes, 100mm x 100mm (Wall mount sold separately)

Connectivity

Video Graphics Array (VGA)

Security

Security port (cable lock sold separately)
Anti-theft stand lock slot (to panel)

COLOR, SIZE AND WEIGHT

Color
CIE 1976 (82%) and CIE 1931 (72%) test standards
Preset Display Area (H X V)
Horizontal - 409.8 mm (16.4 inches) x 230.4 mm (9.07 inches)
Dimensions with stand (H x W x D)
349.10 mm x 445.41 mm x 163.78 mm
13.74 inches x 17.54 inches x 6.45 inches
Dimensions without stand (H x W x D)
266.05 mm x 445.41 mm x 52.30 mm
10.47 inches x 17.54 inches x 2.06 inches
Weight (panel only - for VESA mount)
2.64 Kg (5.82 lbs)
Weight (with packaging)
3.94 Kg (8.69 lbs)

Environmental

Temperature Range Operating:
0° to 40 ° C (32° to 104°F)
Temperature Range Non-operating:
Storage: -20° to 60° C (-4° to 140° F)
Shipping: -20° to 60° C (-4° to 140° F)
Humidity Range Operating:
10 - 80% (non-condensing)
Humidity Range Non-operating:
Storage: 5% to 90% (non-condensing)
Shipping: 5% to 90% (non-condensing)
Altitude Operating:
4485 m (14,700 ft) max
Altitude Non-operating:
12,191 m (40,000 ft) max