

Tech Specs & Customization

Display

Diagonal Viewing Size:

55.87 cm 22.0 Inches

Preset Display Area (H x V)

473.76 mm x 296.10 mm 18.65"x 11.66" 140280 mm² (217.43 inches²)

Panel Type:

Twisted Nematic

Display Screen Coating

Antiglare with 3H hardness

Maximum Preset Resolution

1680 x 1050 at 60Hz

Viewing Angle

(178° vertical / 178° horizontal)

Pixel Pitch

0.282mm x 0.282 mm

Pixel Per Inch (PPI)

90

Contrast Ratio

1000: 1 (typical) 4 Million: 1 (Dynamic)

Aspect Ratio

(16:10)

Backlight Technology

LED

Brightness

250 cd/m² (typical)

Response Time

5 ms (black to white)

Wireless Charging Feature

NA

G-SYNC Suupport

NA

Adjustability

Height-adjustable stand (130mm),

Tilt (-5° to 21°)
Swivel (45° to 45°)
Pivot (90° clockwise)
Built in cable-management

PbP / PiP

PbP (No) PiP (No)

Daisy Chain Availability

No

Dell Display Manager Compatibility

Yes

Remote Asset Management

Yes, via Dell Command | Monitor

Color Support

Color Gamut (typical): 84% (CIE 1976), 72% (CIE 1931)

Color Depth: 16.7 Million colors

Color Calibration SDK SW

No

Color Calibration with X-rite colorimeter

No

Flat Panel Mount Interface

VESA (100 mm)

Audio Output

Optional Soundbar - (AC511)

Connectivity

1 x DP (ver 1.2)

1 x HDMI (ver 1.4)

1 x VGA

1 x USB 3.0 port - Upstream

2 x USB 3.0 ports - Side

2X USB 2.0 - bottom.

Built-in Devices

USB3.0 super-Speed Hub (with 1 x USB upstream port,

2 x USB3.0 and 2 x USB2.0 downstream ports)



Tech Specs & Customization

Dimensions

Height with stand (Compressed ~ Extended)

367.4 mm ~497.4 mm 14.46" ~19.58"

Width

503.4 mm

19.82"

Depth

180.0mm

7.09 inches

Height without stand

330.4 mm

13.01"

Width without stand

503.4 mm

19.82"

Depth without stand

50.3mm

1.98"

Weight (panel only - for VESA mount)

3.00 kg

6.61 lb

Weight (with packaging)

7.03 kg

15.49 lb

Power

Voltage Required

100 to 240 VAC / 50 or 60 Hz \pm 3Hz / 1.5 A (typical)

Power Consumption (Operational)

18W (typical) /45W (maximum)**/48.5 kWh (Energy Star)

Power Consumption Stand by / Sleep

Less than 0.3W

Environmental

Temperature Range Operating

Operating: 0° to 40°C (32° to 104°F) Non-operating: -20° to 60° (-4° to 140° F)

Humidity Range Operating

Operating: 10% to 80% (non-condensing)
Non-Operating:5% to 90% (non-condensing)

Altitude Operating

Operating: 5,000 m (16,400 ft) max Non-Operating: 12,191 m (40,000 ft) max