

## Panel

Screen Size	55" Class (54.64" measured diagonal)
Native Resolution	1,920 x 1,080 (FHD), M+

---

## Connectivity

Input	HDMI, DP, DVI-D, Audio
Output	DP, External Speaker (*waterproof speakers are mandatory for outdoor installation)
External Control	RS232C, RJ45, SD Card, USB 3.0

---

## Physical Specification

Bezel Width	66.4 mm (T/B), 31.0 mm (L/R)
Monitor Dimension (W x H x D)	745.3 x 1,345.4 x 160.0 mm
Weight (Head)	70 kg

---

## Environment Conditions

Operation Temperature	-30 °C to 50 °C
Operation Humidity	5 % to 100 %

---

## Power

Power Supply	100-240V~, 50/60Hz
Power Type	Built-In Power

---

## Standard (Certification)

Safety	UL / cUL / CB
EMC	FCC Class "A" / CE / KCC
ErP / Energy Star	No / No

---

## Media Player Compatibility

OPS type compatible	No
External Media player Attachable	No

---

## Software Compatibility

Content Management Software	SuperSign Premium
Control and Monitoring Software	SuperSign C

---

## Accessory

Basic	Remote controller, EIG, ESG, Regulation book, Phone to RS232C gender, USB cable, HDMI cable
Optional	Media player (driven by customer), Enclosure Stand (ST-550X)

---