



KYOCERA Document Solutions Europe

[> Home](#) > [Products](#) > [ECOSYS M5521cdw - Technical Specification](#)


ECOSYS M5521cdw

[Product Information](#)
[Product Views](#)
[Related Products](#)
[Technical Specification](#)

GENERAL

General type	Colour multifunctional for A4 format
Technology	KYOCERA ECOSYS, Colour Laser
Engine speed	Up to 21 pages A4 per minute in colour and b/w
Resolution	1,200 x 1,200 dpi print at reduced speed, multibit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan/copy)
Warm-up time	Approx. 32 seconds or less
Time to first print	Approx. 11/12.5 seconds or less in b/w / colour
Time to first copy	Approx. 10/12 seconds or less in b/w / colour
Dimensions (W x D x H)	417 x 429 x 495 mm
Weight	Approx. 26 kg including toner container
Power consumption	Printing: 345 W, Ready mode: 41 W, Sleep-mode: 1 W
Power source	AC 220 ~ 240 V, 50/60 Hz
Noise (ISO 7779)	Noise level (sound pressure level ISO 7779/ISO 9296) Printing (BW/Colour) 46.2 dB(A) LpA, Stand-by: Immeasurably low Sleep mode: Immeasurably low
Safety standards	TÜV/GS, CE - This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	Standard 512 MB, max. 1,536 MB

PAPER HANDLING

Input capacity	50-sheet multi-purpose tray; 60–220 g/m ² ; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60–163 g/m ² ; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356mm).
Max. input capacity with options	550 sheets
Duplex unit	Duplex as standard: Double-sided printing: 60 – 120 g/m ² ; A4, A5, B5, Letter, Legal
Max. output capacity	150 sheets face-down with paper full detection
Document processor	50-sheet, 50–160 g/m ² , A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm to 216 x 356 mm)
General paper handling	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

PRINT

Processor	800MHz
-----------	--------

Controller language	PRESCRIBE IIc
Emulations	PCL 6 (PCL 5c/PCL-XL), PostScript 3 (PDL 3), PDF Direct Print 1.7, XPS Direct Print
Fonts	93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
Applicable OS	All current Windows operating systems, MAC OS X Version 10.8 or higher, Unix, Linux as well as other operating systems on request

COPY

Max. original size	A4/legal
Digital copy features	Auto Colour Mode, Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, priority print, program, auto duplex copy, continuous scan, auto cassette change, copy density control
Exposure modes	Manual: 9 steps
Preset magnification ratios	7 Reductions/5 Enlargements
Zoom range	25 - 400 % in 1% steps
Continuous copy	1 - 999
Image adjustments	Text + Photo, Photo, Text, Map, Printed document

SCAN

Compression format	MMR/JPEG
File type	TIFF, PDF, PDF/A , high compression PDF, encrypted PDF, JPEG, XPS
Scan features	Integrated address book, Active directory support, encrypted data transfer, Blank sheet skip
Original recognition	Text + Photo, Photo, Text, Light Text, Text (for OCR)
Max. scan size	A4 / legal
Scan functionalities	Scan-to-e-mail (SMTP), Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)
Scan resolution	600, 400, 300, 200 dpi (256 grey scales per colour)
Scan speed	30 ipm (300 dpi, A4, b/w), 23 ipm (300 dpi, A4, colour)

FAX

Compatibility	ITU-T Super G3
Modem speed	Max. 33.6 kbps
Scanning speed	2 seconds /sheet or less
Transmission speed	3 seconds or less
Scanning density	Normal: 200 x 100 dpi, Fine: 200 x 200 dpi, Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi
Max. original size	A4 / legal
Compression method	JBIG, MMR, MR, MH
Fax features	Network fax, duplex transmission and reception, polling transmission and reception

INTERFACES

Standard interface	USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN, Slot for optional SD/SDHC-Card
--------------------	--

WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.
----------	---

RELATED DOWNLOADS

- [↗ ECOSYS M5521cdw documentation](#)
- [↗ ECOSYS M5521cdw driver](#)
- [↗ ECOSYS M5521cdw software](#)
- [↗ ECOSYS M5521cdw datasheet](#)

RELATED LINKS

- [↗ Product Configurator](#)

RELATED VIDEO



