



KYOCERA Document Solutions Europe

[> Home](#) > [Products](#) > [ECOSYS P6130cdn - Technical Specification](#)


# ECOSYS P6130cdn

[Product Information](#)
[Product Views](#)
[Related Products](#)
[Technical Specification](#)

## GENERAL

General type	Colour Printer for A4 format
Technology	KYOCERA ECOSYS, Colour Laser
Engine speed	Up to 30 pages per minute in A4 in colour and b/w
Resolution	600 x 600 dpi, MultiBit-Technology for print quality of up to 9,600 x 600 dpi
Warm-up time	Approx. 26 seconds or less from power on
Time to first print	Approx. 7 seconds or less in b/w, Approx. 8 seconds or less in colour
Dimensions (W x D x H)	390 x 523 x 409.5 mm
Weight	Approx. 28 kg
Power consumption	Printing: 479 W, Ready mode: 56 W, Sleep-mode: 2 W
Power source	220 ~ 240 V, 50/60 Hz
Noise (ISO 7779)	Noise (Sound pressure level: ISO 7779 / ISO 9296) Printing in colour: 49.2 dB(A) LpA, Quiet mode in colour: 46,3 dB(A) LpA, Sleep-mode: Immeasurable low
Safety standards	GS, TÜV, CE - This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	Standard: 512 MB RAM, max. 2,048 MB RAM

## PAPER HANDLING

Input capacity	Max. 100-sheet multi-purpose tray, 60–220 g/m <sup>2</sup> , A4, A5, A6, B5,B6, letter, legal, folio, custom (70 x 148 to 216 x 356 mm); max. 500-sheet universal paper cassette, 60–163 g/m <sup>2</sup> , A4, A5, A6, B5, B6, letter, legal, custom (105 x 148 to 216 x 356 mm)
Max. input capacity with options	2,100 sheets
Duplex unit	Double-side printing as standard; 60–163 g/m <sup>2</sup> ; A4, A5, B5, Letter, Legal
Max. output capacity	250-sheet face-down with paper full sensor
General paper handling	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

## PRINT

Processor	PowerPC 465S/1 GHz
Controller language	PRESCRIBE IIc
Emulations	PCL 6 (PCL 5c/PCL-XL), PostScript 3 (KPD L 3), PDF Direct Print 1.7, XPS Direct Print

Fonts	93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 Bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
Integrated Accounting	100 department codes
Features	Security features: IPSec, HTTPS, SNMPv3, IPPS, Encrypted PDF Direct Print, Private Print, Secure printing via SSL, POP over SSL, SMTP over SSL, Access control via 100 integrated department codes Data Security Kit (E) protects data on the optional SSD.
Protocol	Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria
Applicable OS	All current Windows operating systems, Mac OS X Version 10.5 or higher, UNIX, LINUX as well as other operating systems on request

## INTERFACES

Standard interface	USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/ 1000BaseT) Slot for optional internal print server or SSD hard disc Slot for optional SD/SDHC-Card
--------------------	---

## WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drums and developers for 3 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.
----------	---

## RELATED DOWNLOADS

- [↻ ECOSYS P6130cdn documentation](#)
- [↻ ECOSYS P6130cdn software](#)
- [↻ ECOSYS P6130cdn driver](#)
- [↻ ECOSYS P6130cdn datasheet](#)

## ↻ Product video

## RELATED LINKS

- [🔗 Product Configurator](#)

[🔗 This website uses cookies. You can change your cookie settings in your web browser settings. If you like to know more, click here.](#)

- [🔗 Printing Economy Check](#)

- [↻ Pantone Office for KYOCERA](#)



[↻ Continue](#)

[> Sitemap](#) [> Legal Notices & Terms](#) [> KYOCERA cookie usage](#)

© KYOCERA Document Solutions Europe B.V.