

ePDU G3 platform model selection guide

	Catalog Number	Function	Plug	Breaker	Max kW	Cord (ft)	Output receptacles	Dimensions (H x W x D, in)
ePDU G3 Basic models selection guide	EBA301-10	BA	L15-20P	(3) 20A	5.76	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
	EBA311-10	BA	L15-20P	(3) 20A	5.76	10	(42) C13	69.5 x 2.05 x 2.1
	EBA308-10	BA	L21-20P	None	5.76	10	(21) 5-20R, (6) L6-20R	66.5 x 2.05 x 2.1
	EBA309-10	BA	L21-20P	None	5.76	10	(39) 5-20R	66.5 x 2.05 x 2.1
	EBA302-10	BA	L21-20P	(3) 20A	5.76	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
	EBA312-10	BA	L21-20P	(3) 20A	5.76	10	(42) C13	69.5 x 2.05 x 2.1
	EBA303-10	BA	L15-30P	(3) 20A	8.64	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
	EBA313-10	BA	L15-30P	(3) 20A	8.64	10	(42) C13	69.5 x 2.05 x 2.1
	EBA310-10	BA	L21-30P	(3) 20A	8.64	10	(30) C13, (6) C19, (1) 5-20R	66.5 x 2.05 x 2.1
	EBA304-10	BA	L21-30P	(3) 20A	8.64	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
	EBA314-10	BA	L21-30P	(3) 20A	8.64	10	(42) C13	69.5 x 2.05 x 2.1
	EBA305-06	BA	CS8365	(3) 20A	12.48	6	(30) C13, (6) C19	66.5 x 2.05 x 2.1
	EBA315-10	BA	CS8365	(3) 20A	12.48	10	(42) C13	69.5 x 2.05 x 2.1
	EBA300-06	BA	CS8365	(2) 20A, (1) 30A	14.4	6	(24) C13, (4) C19, (2) L6-30P	66.5 x 2.05 x 2.1
	EBA306-06	BA	CS8365	(6) 20A	14.4	6	(21) C13, (12) C19	66.5 x 2.05 x 2.1
	EBA307-06	BA	IEC60309 460P9	(6) 20A	17.3	6	(21) C13, (12) C19	66.5 x 2.05 x 2.1
	ePDU G3 Metered Input models selection guide	EMI100-10	MI	5-15P	None	1.44	10	(24) 5-15R
EMI101-10		MI	L5-20P (5-20P adapter)	None	1.92	10	(24) 5-20R	66.5 x 2.05 x 2.1
EMI102-10		MI	L5-30P	(2) 20A	2.88	10	(30) 5-20R	66.5 x 2.05 x 2.1
EMI103-10		MI	C20 (L6-20 adapter)	None	3.84	10	(18) C13, (2) C19	35.5 x 2.05 x 2.1
EMI301-10		MI	L15-20P	(3) 20A	5.76	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
EMI311-10		MI	L15-20P	(3) 20A	5.76	10	(42) C13	69.5 x 2.05 x 2.1
EMI308-10		MI	L21-20P	None	5.76	10	(21) 5-20R, (6) L6-20R	66.5 x 2.05 x 2.1
EMI309-10		MI	L21-20P	None	5.76	10	(39) 5-20R	66.5 x 2.05 x 2.1
EMI318-10		MI	L21-20P	None	5.76	10	(30) C13, (6) C19, (3) 5-20R	66.5 x 2.05 x 2.1
EMI302-10		MI	L21-20P	(3) 20A	5.76	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
EMI312-10		MI	L21-20P	(3) 20A	5.76	10	(42) C13	69.5 x 2.05 x 2.1
EMI104-10		MI	L6-30P	(2) 20A	5.76	10	(36) C13, (6) C19	66.5 x 2.05 x 2.1
EMI303-10		MI	L15-30P	(3) 20A	8.64	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
EMI313-10		MI	L15-30P	(3) 20A	8.64	10	(42) C13	69.5 x 2.05 x 2.1
EMI310-10		MI	L21-30P	(3) 20A	8.64	10	(30) C13, (6) C19, (1) 5-20R	66.5 x 2.05 x 2.1
EMI304-10		MI	L21-30P	(3) 20A	8.64	10	(30) C13, (6) C19	66.5 x 2.05 x 2.1
EMI314-10		MI	L21-30P	(3) 20A	8.64	10	(42) C13	69.5 x 2.05 x 2.1
EMI305-06		MI	CS8365	(3) 20A	12.48	6	(30) C13, (6) C19	66.5 x 2.05 x 2.1
EMI315-10		MI	CS8365	(3) 20A	12.48	10	(42) C13	69.5 x 2.05 x 2.1
EMI300-06		MI	CS8365	(2) 20A, (1) 30A	14.4	6	(24) C13, (4) C19, (2) L6-30R	66.5 x 2.05 x 2.1
EMI316-06	MI	CS8365	(6) 20A	14.4	6	(9) C13, (12) C19	66.5 x 2.05 x 2.1	
EMI317-06	MI	IEC60309 460P9	(6) 20A	17.3	6	(9) C13, (12) C19	66.5 x 2.05 x 2.1	

Eaton
Electrical Sector
1000 Eaton Boulevard
Cleveland, OH 44122 USA
Eaton.com

© 2014 Eaton
All Rights Reserved
Printed in USA
BR155001EN
January 2014

Eaton, Intelligent Power and ePDU are registered trademarks of Eaton.

All other trademarks are property of their respective owners.

For more information
about the new ePDU
G3 platform, visit
Eaton.com/ePDUG3