

KEW **1018/1018H****1018 (Soft case type) / 1018H (Hard case type)**

- Display : 4000 counts.
- Auto range.
- Diode test feature.
- Capacitance test feature.
- Continuity test.



DC V	400mV/4/40/400/600V (Input Impedance 10MΩ) ±0.8%rdg±5dgt (400mV/4/40/400V) ±1.0%rdg±5dgt (600V)
AC V	4/40/400/600V (Input Impedance 10MΩ) ±1.3%rdg±5dgt (4/40V) ±1.6%rdg±5dgt (400/600V)
Ω	400Ω/4/40/400kΩ/4/40MΩ ±1.0%rdg±5dgt (400Ω/4/40/400kΩ/4MΩ) ±2.5%rdg±5dgt (40MΩ)
Continuity buzzer	400Ω (Buzzer sounds below 120Ω)
Diode test	4V Release Voltage: Approx. 0.4mA Test Current
Capacitance	4nF/40nF/400nF/4μF/40μF/200μF
Frequency	10/100Hz/1/10/100/200kHz
Applicable standards	IEC 61010-1 CAT III 300V IEC 61010-2-031 IEC 61326-1
Display	4000 counts
Power source	LR44 (1.5V) × 2
Dimensions	107(L) × 54(W) × 10(D)mm
Weight	70g approx.
Included Accessories	LR44 × 2 Instruction Manual 1018 (Soft Case) 1018H (Hard Case)