

MODEL 1110



- High sensitivity DC20k Ω /V.
- 1m drop-proof heavy duty designed taut-band movement.
- Can measure line voltage up to AC 600V.
(Voltage to ground MAX AC300V)
(Protected by 600V ceramic fuse against accidental overload)
- Continuity buzzer, battery check, LED check function.
- Skeleton type robust and clear case
with carrying handle furnished as standard accessory.



DC V	0.3V (16.7k Ω /V) \pm 3% of FS 3/12/30/120/300/600V (20k Ω /V) \pm 3% of FS
AC V	12V (9k Ω /V) \pm 4% of FS 30/120/300/600V (9k Ω /V) \pm 3% of FS
DC A	60 μ A/30/300mA \pm 3% of FS
Ω	3/30/300k Ω \pm 3% of scale length
Continuity buzzer	Buzzer sounds below 100 Ω
Battery Test	1.5V (0.7 - 2V) \pm 3% of FS (10 Ω load)
Temperature	Note: The MODEL1110 includes a temperature measurement scale, but it is not available for new customers due to the discontinue of the Temperature Probe 7060.
LED	10mA approx. at 0 Ω (at 3V of battery voltage)
Applicable standards	IEC 61010-1 CAT III 300V Pollution Degree 2 CAT II 600V Pollution Degree 2 IEC 61010-2-031
Power source	R6 (AA) (1.5V) \times 2
Dimensions	140(L) \times 94(W) \times 39(D) mm
Weight	280g approx.
Included Accessories	7066A (Test leads) 8923 (F500mA/600V fuse) \times 2 R6 (AA) \times 2 9103 (Carrying case) Instruction Manual