

KT 203



- Small and handy clamp meter
- IEC 61010-1 Safety Standard CAT III 300V, CAT II 600V
- 400A AC/DC Clamp meter
- DMM function ACV, DCV, Ω , Continuity Buzzer.

CE

 $\phi 30$ MAX
400ADC
AC ADC
AC V Ω

)))

DATA
HOLDAUTO
POWER
SAVE

AC A	40.00/400.0A (Auto-ranging) $\pm 3.0\%rdg\pm 8dgt[50/60Hz](0 - 40.00A)$ $\pm 3.5\%rdg\pm 6dgt[50/60Hz](15.0 - 299.9A)$ $\pm 4.0\%rdg\pm 6dgt[50/60Hz](300.0 - 400.0A)$
DC A	40.00/400.0A (Auto-ranging) $\pm 3.0\%rdg\pm 8dgt (0 - 40.00A)$ $\pm 3.5\%rdg\pm 6dgt (15.0 - 299.9A)$ $\pm 4.0\%rdg\pm 6dgt (300.0 - 400.0A)$
AC V	400.0/600V (Auto-ranging) $\pm 2.0\%rdg\pm 5dgt(50/60Hz)$
DC V	400.0/600V (Auto-ranging) $\pm 1.5\%rdg\pm 5dgt$
Ω	400.0/4000 Ω (Auto-ranging) $\pm 2.0\%rdg\pm 5dgt$
Continuity buzzer	buzzer sounds below $50\pm 35\Omega$
Conductor size	$\phi 30mm$ max.
Applicable standards	IEC 61010-1 CAT III 300V(ACA), CAT II 600V Pollution degree 2 IEC 61010-2-032, IEC 61326-1
Power source	R03(1.5V)(AAA) $\times 2$ *Continuous measuring time: Approx. 35 hours (Auto power save: approx. 10 minutes)
Dimensions	187(L) \times 68.5(W) \times 38.5(D)mm
Weight	Approx. 200g(including batteries)
Included Accessories	7066A (Test leads) R03 (AAA) $\times 2$, Instruction Manual
Optional Accessories	9105 (Carrying case)